



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier** CODE 3002
- **Trade name:** SWIN Etch Primer
- **Article number:** 10-213-*
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**
 PROC11 Non industrial spraying
 PROC7 Industrial spraying
- **Environmental release category** ERC8c Widespread use leading to inclusion into/onto article (indoor)
- **Application of the substance / the mixture** Coating material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 SWIN Lacksysteme
 Boschweg 5
 D-48351 Everswinkel
 info@swinsysteme.de
- **Further information obtainable from:**
 Laboratory department
 +49 2582-67613 / +49 2582-67677
- **Emergency telephone number:** Giftnotruf Berlin: ++49 (0) 30 19240

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 1)

Hazard pictograms

GHS02 GHS05 GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:**

butan-1-ol

xylene

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight > 700 - <1100)

chromium orthophosphate

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards -**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterisation: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38-XXXX	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	10-25%
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight > 700 - <1100) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-10%

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 2)

CAS: 7789-04-0 Reg.nr.: 01-212074781-54	chromium orthophosphate ⚠ Skin Sens. 1, H317	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	≤2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:** Personal protection for the First Aider.
- **After inhalation:**
Supply fresh air.
Seek medical treatment in case of complaints.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
Seek medical treatment.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep receptacles tightly sealed.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 3)

Ensure good ventilation/exhaustion at the workplace.

Restrict the quantity stored at the work place.

· **Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.

Suitable material for receptacles and pipes: steel or stainless steel.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store receptacle in a well ventilated area.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

Sk

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 4)

Preventive skin protection by use of skin-protecting agents is recommended.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

Value for the permeation: Level ≤ 1

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact \Rightarrow 480 minutes gloves made of the following materials are suitable:**

HPPE-laminated film (Ansell Barrier®)

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**

Protective clothing, anti-static (TYVEK® CLASSIC PLUS)

Safety shoes/boots, antistatic

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Aromatic
Odour threshold:	Not determined.

· **pH-value** Not applicable.

· **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	116 °C

· **Flash point:** < 23 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 340 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:	1.1 Vol %
Upper:	9.4 Vol %

Vapour pressure at 20 °C:	6.7 hPa
Relative density	0,95 - 1,05
Vapour density	-
Evaporation rate	Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 5)

- | | |
|--|--|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic at 20 °C: | 70 s (DIN 53211/4) |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Respiratory or skin sensitisation**
 - Persons already sensitised to may develop allergic reactions when using this product.
 - Persons suffering from asthma, eczema or skin problems should avoid contact with this product.
- **May cause an allergic skin reaction.**
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 6)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- **Uncleaned packaging:**
15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00: packaging (including separately collected municipal packaging waste)
15 01 10*: packaging containing residues of or contaminated by dangerous substances
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT

- **Transport hazard class(es)**
- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids.

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 7)

· Label	3
· Packing group · ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, S-E B
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.12.2020

Version number 1

Revision: 01.12.2020

Trade name: SWIN Etch Primer

(Contd. of page 8)

*H318 Causes serious eye damage.**H319 Causes serious eye irritation.**H332 Harmful if inhaled.**H335 May cause respiratory irritation.**H336 May cause drowsiness or dizziness.**H373 May cause damage to organs through prolonged or repeated exposure.*· **Department issuing SDS:** -· **Contact:** -· **Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity - oral – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1*

GB