



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1

Revision: 26.05.2015

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** SWIN HS FÜLLER LICHTGRAU
- **Article number:** 20-107-*
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category PC9a** Coatings and paints, thinners, paint removers
- **Process category**
 PROC7 Industrial spraying
 PROC11 Non industrial spraying
- **Environmental release category**
 ERC8c Wide dispersive indoor use resulting in inclusion into or onto a matrix
- **Application of the substance / the mixture** Coating material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 SWIN Lacksysteme
 Boschweg 5
 D-48351 Everswinkel
 info@swinsysteme.de
- **Further information obtainable from:** +49 2582-67613 / +49 2582-67677
- **Emergency telephone number:** Giftnotruf Berlin: ++49 (0) 30 19240

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02

- **Signal word** Warning
- **Hazard statements**
 H226 Flammable liquid and vapour.
 H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 P260 Do not breathe mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards** -

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1

Revision: 26.05.2015

Trade name: SWIN HS FÜLLER LICHTGRAU

(Contd. of page 1)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; STOT SE 3, H335	10-25%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	2.5-10%
EC number: 918-668-5 Reg.nr.: 01-02119455851-35-XXXX	Hydrocarbons, C9-C15, Aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	≤ 2.5%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	≤ 2.5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:** Personal protection for the First Aider.
- **After inhalation:**
Supply fresh air.
Seek medical treatment in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1

Revision: 26.05.2015

Trade name: SWIN HS FÜLLER LICHTGRAU

(Contd. of page 2)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Restrict the quantity stored at the work place.
- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Flammable gas-air mixtures may form in empty receptacles.
Keep ignition sources away - Do not smoke.
Use explosion-proof apparatus / fittings and spark-proof tools.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Provide solvent resistant, sealed floor.
Suitable material for receptacles and pipes: steel or stainless steel.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1

Revision: 26.05.2015

Trade name: SWIN HS FÜLLER LICHTGRAU

(Contd. of page 3)

· **Ingredients with biological limit values:**

1330-20-7 xylene

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P2

· **Protection of hands:**

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

Value for the permeation: Level ≤ 1

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact => 480 minutes gloves made of the following materials are suitable:**

HPPE-laminated film (Ansell Barrier®)

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**

Protective clothing, anti-static (TYVEK® CLASSIC PLUS)

Safety shoes/boots, antistatic

GB

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1

Revision: 26.05.2015

Trade name: SWIN HS FÜLLER LICHTGRAU

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
· Form:	Fluid
· Colour:	Light grey
· Odour:	Product specific
· Odour threshold:	Not determined.
· pH-value: Not determined.	
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	124 °C
· Flash point: 21 - 55 °C	
· Flammability (solid, gaseous): Not applicable.	
· Ignition temperature: 450 °C	
· Decomposition temperature: Not determined.	
· Self-igniting: Product is not selfigniting.	
· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits:	
· Lower:	0.7 Vol %
· Upper:	7.5 Vol %
· Vapour pressure at 20 °C: 5 hPa	
· Density at 20 °C: 1.44 g/cm ³	
· Relative density Not determined.	
· Vapour density Not determined.	
· Evaporation rate Not determined.	
· Solubility in / Miscibility with water: Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity: DIN 53211 (6 mm) - 65 sec	
· Dynamic: Not determined.	
· Kinematic: Not determined.	
· Solvent content:	
· VOC (EC)	30.60 %
· Solids content: 69.4 %	
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 6)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1

Revision: 26.05.2015

Trade name: SWIN HS FÜLLER LICHTGRAU

(Contd. of page 5)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:****64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
----------	---

08 01 00	wastes from MFSU and removal of paint and varnish
----------	---

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

· **Uncleaned packaging:**

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00: packaging (including separately collected municipal packaging waste)

(Contd. on page 7)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1


Revision: 26.05.2015

Trade name: SWIN HS FÜLLER LICHTGRAU

15 01 10*: packaging containing residues of or contaminated by dangerous substances

(Contd. of page 6)

14 Transport information

· UN-Number	not regulated
· ADR, ADN, IMDG	not regulated
· IATA	UN1263
· UN proper shipping name	not regulated
· ADR, ADN, IMDG	not regulated
· IATA	PAINT
· Transport hazard class(es)	
· ADR, ADN, IMDG	
· Class	not regulated
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADR, IMDG	not regulated
· IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Remarks:	No dangerous goods in containers of 450 litres max. capacity acc. to ADR 2.2.3.1.5
· IMDG	
· Remarks:	No dangerous goods in containers of 30 litres max. capacity acc. to IMDG 2.2.3.1.5
· UN "Model Regulation":	-

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
No further relevant information available.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 1

Revision: 26.05.2015

Trade name: SWIN HS FÜLLER LICHTGRAU

(Contd. of page 7)

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing MSDS: -**

· **Contact: -**

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

GB