



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier** CODE 3003
- **Trade name:** SWIN FÜLLER HÄRTER
- **Article number:** 30-900-*
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category**
 PROC7 Industrial spraying
 PROC11 Non industrial spraying
- **Environmental release category** ERC8c Widespread use leading to inclusion into/onto article (indoor)
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 SWIN Lacksysteme
 Boschweg 5
 D-48351 Everswinkel
 info@swinsysteme.de
- **Further information obtainable from:** +49 2582-67613 / +49 2582-67677
- **Emergency telephone number:** Giftnotruf Berlin: ++49 (0) 30 19240

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

xylene

Toluene diisocyanate, aromatisches Polyisocyanat

ethylbenzene

m-tolyldiene diisocyanate

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards -

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	50-100%
CAS: 53317-61-6	Toluene diisocyanate, aromatisches Polyisocyanat ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-10%

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 2)

CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119892111-44-XXXX	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	≤2.5%
CAS: 26471-62-5 EINECS: 247-722-4 Reg.nr.: 01-2119454791-34-XXXX	m-tolylidene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≤2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **Description of first aid measures**
- **General information:** Personal protection for the First Aider.
- **After inhalation:**
Supply fresh air.
Seek medical treatment in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 3)

Restrict the quantity stored at the work place.
TRGS 430 Isocyanate - Exposition und Überwachung beachten.

· **Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.
Flammable gas-air mixtures may form in empty receptacles.
Keep ignition sources away - Do not smoke.
Use explosion-proof apparatus / fittings and spark-proof tools.
Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.
Suitable material for receptacles and pipes: steel or stainless steel.

· **Information about storage in one common storage facility: Not required.**

· **Further information about storage conditions: Keep container tightly sealed.**

· **Specific end use(s) No further relevant information available.**

8 Exposure controls/personal protection

· **Additional information about design of technical facilities: No further data; see item 7.**

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
	Sk

26471-62-5 m-tolyldiene diisocyanate

WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

· **Additional information: The lists valid during the making were used as basis.**

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P2

(Contd. on page 5)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 4)

Protection of hands:

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material

Value for the permeation: Level ≤ 1

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact => 480 minutes gloves made of the following materials are suitable:

HPPE-laminated film (Ansell Barrier®)

Eye protection:


Tightly sealed goggles

Body protection:

Protective clothing, anti-static (TYVEK® CLASSIC PLUS)

Safety shoes/boots, antistatic

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information
Appearance:

Form:	Fluid
Colour:	Colourless
Odour:	Aromatic
Odour threshold:	Not determined.

pH-value Not applicable.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	124 °C

Flash point: 23 - 60 °C

Flammability (solid, gas): Not applicable.

Ignition temperature: 315 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 5)

· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapour pressure at 20 °C: 6.7 hPa	
· Relative density Not determined.	
· Vapour density Not determined.	
· Evaporation rate Not determined.	
· Solubility in / Miscibility with water: Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water: Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	12 s (DIN 53211/4)
· Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.

· LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
 - Persons already sensitised to may develop allergic reactions when using this product.
 - Persons suffering from asthma, eczema or skin problems should avoid contact with this product.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 6)

- **Aspiration hazard**
May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- **Uncleaned packaging:**
15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00: packaging (including separately collected municipal packaging waste)
15 01 10*: packaging containing residues of or contaminated by dangerous substances
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **ADR** 1263 PAINT RELATED MATERIAL
- **IMDG, IATA** PAINT RELATED MATERIAL

(Contd. on page 8)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 7)

· **Transport hazard class(es)**· **ADR, IMDG, IATA**· **Class** 3 Flammable liquids.· **Label** 3· **Packing group**· **ADR, IMDG, IATA** III· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user** Warning: Flammable liquids.· **Danger code (Kemler):** 30· **EMS Number:** F-E,S-E· **Stowage Category** A· **Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category** 3· **Tunnel restriction code** D/E· **IMDG**· **Limited quantities (LQ)** 5L· **Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category P5c** FLAMMABLE LIQUIDS· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

(Contd. on page 9)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.02.2019

Version number 1

Revision: 08.02.2019

Trade name: SWIN FÜLLER HÄRTER

(Contd. of page 8)

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

• **Department issuing SDS:** -

• **Contact:** -

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3