

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-101-6  
Universal thinner normal  
Revision date : 09.11.2021  
Print date : 10.11.2021  
Version (Revision) : 8.0.0 (7.0.0)

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

SWIN 60-101-6  
Universal thinner normal (24799)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Coatings and paints, thinners, paint removers Washing and cleaning products

#### 1.3 Details of the supplier of the safety data sheet

##### Supplier (manufacturer/importer/only representative/downstream user/distributor)

SWIN Lacksysteme  
Inh. Ludwig Schöne e.K

Street : Boschweg 5

Postal code/city : 48351 Everswinkel

Telephone : +49(0)2582/67613

Telefax : +49(0)258267677

Information contact : info@swinsysteme.de

#### 1.4 Emergency telephone number

Giftinformationszentrum Göttingen (GIZ-Nord) Phone: +49 (0)551-19240

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

##### Signal word

Danger

##### Hazard components for labelling

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

N-BUTYL ACETATE ; CAS No. : 123-86-4

XYLENE ; CAS No. : 1330-20-7

ETHYLBENZENE ; CAS No. : 100-41-4

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-101-6  
Universal thinner normal

Revision date : 09.11.2021

Print date : 10.11.2021

Version (Revision) : 8.0.0 (7.0.0)

### Hazard statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapours/spray.  
P310 Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/container to disposal.

### 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

2-METHOXY-1-METHYLETHYL ACETATE ; REACH No. : 01-2119475791-29 ; EC No. : 203-603-9; CAS No. : 108-65-6

Weight fraction :  $\geq 25 - < 50$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336  
Substance with a Community workplace exposure limit

N-BUTYL ACETATE ; REACH No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction :  $\geq 25 - < 50$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

XYLENE ; REACH No. : 01-2119488216-32 ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction :  $\geq 20 - < 25$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

ETHYLBENZENE ; EC No. : 202-849-4; CAS No. : 100-41-4

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H332

2-METHOXYPROPYL ACETATE ; EC No. : 274-724-2; CAS No. : 70657-70-4

Weight fraction :  $< 0,3$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Repr. 1B ; H360D STOT SE 3 ; H335

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove affected person from the danger area and lay down. Observe risk of aspiration if vomiting occurs. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

#### Following inhalation

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

**Print date :** 10.11.2021

Inhalation of vapours or spray/mists

Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Provide fresh air.

### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

### After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting. Call a physician immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

Dizziness Headache Nausea Impairment of vision Vomiting

## 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

Full water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic Carbon monoxide Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

Do not inhale explosion and combustion gases.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### 5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

#### For non-emergency personnel

Use personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### For emergency responders

Use appropriate respiratory protection. Remove persons to safety. Prevent spread over a wide area (e.g. by containment or oil barriers).

### 6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

### 6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

### 6.4 Reference to other sections

Safe handling: see section 7

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

Disposal: see section 13  
Personal protection equipment: see section 8

### SECTION 7: Handling and storage



#### 7.1 Precautions for safe handling

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment (refer to section 8). Avoid: generation/formation of aerosols

It is recommended to design all work processes always so that the following is excluded: Inhalation Skin contact Eye contact

#### Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists  
Skin contact Eye contact Take precautionary measures against static discharges.

#### Measures to prevent fire

Keep away from sources of ignition - No smoking. Usual measures for fire prevention. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only antistatically equipped (spark-free) tools. Wear anti-static footwear and clothing Take precautionary measures against static discharges.

#### Measures to prevent aerosol and dust generation

Vapours/aerosols must be exhausted directly at the point of origin. Use only in well-ventilated areas.

#### Environmental precautions

Shafts and sewers must be protected from entry of the product.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Hints on joint storage

**Storage class (TRGS 510) :** 3

##### Further information on storage conditions

Keep container tightly closed. Keep/Store only in original container.

#### 7.3 Specific end use(s)

Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational exposure limit values

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 50 ppm / 270 mg/m<sup>3</sup>

Peak limitation : 1(I)

Remark : Y

Version : 29.03.2019

Limit value type (country of origin) : STEL ( EC )

Limit value : 100 ppm / 550 mg/m<sup>3</sup>

Remark : H

Version : 20.06.2019

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 275 mg/m<sup>3</sup>  
Remark : H  
Version : 20.06.2019

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 62 ppm / 300 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 29.03.2019

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 50 ppm / 220 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H  
Version : 29.03.2019

Limit value type (country of origin) : STEL ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : H  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 221 mg/m<sup>3</sup>  
Remark : H  
Version : 20.06.2019

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 88 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : H, Y  
Version : 29.03.2019

Limit value type (country of origin) : STEL ( EC )  
Limit value : 200 ppm / 884 mg/m<sup>3</sup>  
Remark : H  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 100 ppm / 442 mg/m<sup>3</sup>  
Remark : H  
Version : 20.06.2019

2-METHOXYPROPYL ACETATE ; CAS No. : 70657-70-4

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 5 ppm / 28 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : H, Z  
Version : 29.03.2019

### Biological limit values

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Methylhippuric acid / Urine (U) / End of exposure or end of shift  
Limit value : 2000 mg/l  
Version : 29.03.2019

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid + Phenylglyoxy acid / Urine (U) / End of exposure or end of shift  
Limit value : 250 mg/g Kr

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

Version : 29.03.2019

### DNEL-/PNEC-values

#### DNEL/DMEL

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 600 mg/m<sup>3</sup>

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 300 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 600 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 300 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 11 mg/kg

Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 11 mg/kg

XYLENE ; CAS No. : 1330-20-7

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 289 mg/m<sup>3</sup>

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 221 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 442 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 211 mg/m<sup>3</sup>

Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 180 mg/kg

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 77 mg/m<sup>3</sup>

#### PNEC

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,18 mg/l

Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,018 mg/l

Limit value type : PNEC (Sediment, freshwater)  
Limit value : 0,981 mg/kg

Limit value type : PNEC (Soil)  
Limit value : 0,0903 mg/kg

Limit value type : PNEC Soil, Marine water  
Limit value : 0,0981 mg/kg

Limit value type : PNEC (Sewage treatment plant)  
Limit value : 35,6 mg/l

XYLENE ; CAS No. : 1330-20-7

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,327 mg/l

Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,327 mg/l

Limit value type : PNEC (Sediment, freshwater)  
Limit value : 12,46 mg/kg

Limit value type : PNEC (Sediment, marine water)  
Limit value : 12,46 mg/kg

Limit value type : PNEC (Sewage treatment plant)  
Limit value : 6,58 mg/l

ETHYLBENZENE ; CAS No. : 100-41-4

Limit value type : PNEC (Aquatic, freshwater)  
Limit value : 0,1 mg/l

Limit value type : PNEC (Aquatic, marine water)  
Limit value : 0,01 mg/l

Limit value type : PNEC (Sediment, freshwater)  
Limit value : 13,7 mg/kg

Limit value type : PNEC (Sediment, marine water)  
Limit value : 1,37 mg/kg

Limit value type : PNEC (Soil)  
Limit value : 2,68 mg/kg

Limit value type : PNEC (Sewage treatment plant)  
Limit value : 9,6 mg/l

### 8.2 Exposure controls



#### Personal protection equipment

##### Eye/face protection

Eye glasses with side protection

##### Skin protection

###### Hand protection

**Suitable material :** Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0.7 mm

Breakthrough time (maximum wearing time)  $10 < x < 30$  min.

Recommended glove articles EN ISO 374

**Remark :** Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. The quality of the protective gloves resistant to chemicals must be chosen

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Body protection

Overall

**Suitable protective clothing :** For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes). Chemical resistant safety shoes Only wear fitting, comfortable and clean protective clothing.

**Required properties :** antistatic. flame-resistant heat-resistant

### Respiratory protection

Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values aerosol or mist formation. spray application

### Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter:

Filter type: A2P2

### General information

Wash hands before breaks and after work. Apply skin care products after work.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Physical state :** Liquid

**Odour :** characteristic

### Appearance

**Colour :** colourless

### Safety characteristics

**Melting point/freezing point :** No data available

**Initial boiling point and boiling range :** ( 1013 hPa ) 124 - 146 °C

**Decomposition temperature :** No data available

**Flash point :** approx. 27 °C DIN 51755 part 1

**Auto-ignition temperature :** approx. 330 °C DIN 51794

**Lower explosion limit :** 1,1 Vol-%

**Upper explosion limit :** 10,8 Vol-%

**Vapour pressure :** ( 20 °C ) approx. 9,6 hPa

**Density :** ( 20 °C ) approx. 0,91 g/cm<sup>3</sup> DIN 51757

**Water solubility :** ( 20 °C ) partially miscible

**pH-value:** ( 20 °C ) not applicable

**Partition coefficient n-octanol/water :** No data available

**Cinematic viscosity :** ( 40 °C ) No data available

**Odour threshold :** No data available

**Relative vapour density :** ( 20 °C ) No data available

**Vapourisation rate :** No data available

**Maximum VOC content (EC) :** 100 Wt % 1999/13/EC

**VOC-value :** 906 g/l 2004/42/EC

**Flammable solids :** Not fulfilling criteria for hazard class "Flammable Solids".

**Flammable gases :** Not applicable.

**Oxidising liquids :** GHS/CLP criteria are not met.

**Explosive properties :** GHS/CLP criteria are not met.



# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

### 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Information is given in subsection 10.3.

### 10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3 Possibility of hazardous reactions

In use, may form flammable/explosive vapour-air mixture.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

Exothermic reaction with:  
Acid , Oxidising agent, strong.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Acute oral toxicity

|                  |   |
|------------------|---|
| Parameter :      | ATEmix calculated                                       |
| Exposure route : | Oral  |
| Effective dose : | not relevant  |
| Parameter :      | LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )           |
| Exposure route : | Oral  |
| Species :        | Rat   |
| Effective dose : | 10760 mg/kg   |
| Method :         | OECD 423  |
| Parameter :      | LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )           |
| Exposure route : | Oral  |
| Species :        | Rabbit  |
| Effective dose : | 7,4 g/kg  |
| Parameter :      | LD50 ( XYLENE ; CAS No. : 1330-20-7 )                   |
| Exposure route : | Oral  |
| Species :        | Rat   |
| Effective dose : | 4300 mg/kg  |
| Parameter :      | LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )              |
| Exposure route : | Oral  |
| Species :        | Rat   |
| Effective dose : | 3500 mg/kg  |
| Parameter :      | LD50 ( 2-METHOXYPROPYL ACETATE ; CAS No. : 70657-70-4 ) |
| Exposure route : | Oral  |
| Species :        | Rat   |
| Effective dose : | 8500 mg/kg  |

#### Acute dermal toxicity

|                  |                   |
|------------------|-------------------|
| Parameter :      | ATEmix calculated |
| Exposure route : | Dermal            |

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

---

Effective dose : 4946 mg/kg  
Parameter : LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 14112 mg/kg  
Method : OECD 402  
Parameter : LD50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 1100 mg/kg  
Parameter : LD50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 12126 mg/kg  
Parameter : ATE ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Dermal  
Effective dose : 1100 mg/kg

**Acute inhalation toxicity**  
Parameter : ATEmix calculated  
Exposure route : Inhalation (vapour)  
Effective dose : 37,1 mg/l  
Parameter : LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Inhalation (vapour)  
Species : Rat  
Effective dose : 21,1 mg/l  
Exposure time : 4 h  
Method : OECD 403  
Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Exposure route : Inhalation (vapour)  
Species : Rat  
Effective dose : 11 mg/l  
Exposure time : 4 h  
Parameter : LC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 11 mg/l  
Exposure time : 4 h  
Parameter : LC50 ( 2-METHOXYPROPYL ACETATE ; CAS No. : 70657-70-4 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 23,88 mg/l

### Corrosive/irritant effect on skin/eyes

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

Based on available data, the classification criteria are not met.

##### Acute (short-term) fish toxicity

Parameter : LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Pimephales promelas (fathead minnow)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 18 mg/l  
Exposure time : 96 h  
Method : OECD 203

Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 2,6 mg/l  
Exposure time : 96 h  
Method : OECD 203

Parameter : LC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 6,4 mg/l  
Exposure time : 48 h

##### Chronic (long-term) fish toxicity

Parameter : Chronic (long-term) fish toxicity ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Evaluation parameter : Chronic (long-term) fish toxicity  
Effective dose : > 1,3 mg/l  
Exposure time : 56 D

##### Acute (short-term) toxicity to crustacea

Parameter : EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) daphnia toxicity  
Effective dose : 44 mg/l  
Exposure time : 48 h  
Method : OECD 202

Parameter : LC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Acute (short-term) daphnia toxicity  
Effective dose : 1 mg/l  
Exposure time : 24 h  
Method : OECD 202

Parameter : EC50 ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Evaluation parameter : Acute (short-term) daphnia toxicity  
Effective dose : 2,4 mg/l  
Exposure time : 48 h

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Print date :** 10.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

### Chronic (long-term) toxicity to crustacea

Parameter : EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 34,2 mg/l  
Exposure time : 21 D  
Method : OECD 211

Parameter : NOAEC ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Daphnia magna (Big water flea)  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 23,2 mg/l  
Exposure time : 21 D  
Method : OECD 211

Parameter : NOEC ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Daphnia pulex (water flea)  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 1,17 mg/l  
Exposure time : 7 D

Parameter : NOEC ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Species : Daphnia pulex (water flea)  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 0,96 mg/l  
Exposure time : 7 D

### Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Selenastrum capricornutum  
Evaluation parameter : Acute (short-term) algae toxicity  
Effective dose : 397 mg/l  
Exposure time : 72 h  
Method : OECD 201

Parameter : EC50 ( XYLENE ; CAS No. : 1330-20-7 )  
Species : Selenastrum capricornutum  
Evaluation parameter : Acute (short-term) algae toxicity  
Effective dose : 2,2 mg/l  
Exposure time : 73 h  
Method : OECD 201

### Chronic (long-term) algae toxicity

Parameter : NOEC ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Selenastrum capricornutum  
Evaluation parameter : Chronic (long-term) algae toxicity  
Effective dose : 196 mg/l  
Method : OECD 201

### Toxicity to other aquatic plants/organisms

Parameter : EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Tetrahymena pyriformis  
Evaluation parameter : Acute (short-term) toxicity  
Effective dose : 356 mg/l  
Exposure time : 40 h

### Toxicity to microorganisms

Parameter : Bacteria toxicity ( XYLENE ; CAS No. : 1330-20-7 )  
Effective dose : 16 mg/l  
Exposure time : 28 D  
Method : OECD F

## 12.2 Persistence and degradability

### Biodegradation

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

**Trade name :** SWIN 60-101-6  
Universal thinner normal

**Revision date :** 09.11.2021

**Version (Revision) :** 8.0.0 (7.0.0)

**Print date :** 10.11.2021

Parameter : Biodegradation ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Inoculum : Biodegradation  
Degradation rate : 83 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).

Parameter : BOD (% of ThOD) ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Inoculum : Degree of elimination  
Evaluation parameter : Aerobic  
Degradation rate : 80 %  
Test duration : 5 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301D

Parameter : Biodegradation ( XYLENE ; CAS No. : 1330-20-7 )  
Inoculum : Biodegradation  
Degradation rate : 90 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301F

Parameter : Biodegradation ( ETHYLBENZENE ; CAS No. : 100-41-4 )  
Inoculum : Biodegradation  
Degradation rate : 90 %  
Test duration : 28 D  
Evaluation : Readily biodegradable (according to OECD criteria).  
Method : OECD 301F

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

**Land transport (ADR/RID)**

PAINT RELATED MATERIAL

**Sea transport (IMDG)**

PAINT RELATED MATERIAL

**Air transport (ICAO-TI / IATA-DGR)**

PAINT RELATED MATERIAL

### 14.3 Transport hazard class(es)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-101-6  
Universal thinner normal  
Revision date : 09.11.2021  
Print date : 10.11.2021

Version (Revision) : 8.0.0 (7.0.0)

### Land transport (ADR/RID)

Class(es) : 3  
Classification code : F1  
Hazard identification number (Kemler No.) : 30  
Tunnel restriction code : D/E  
Special provisions : LQ 5 I · E 1  
Hazard label(s) : 3

### Sea transport (IMDG)

Class(es) : 3  
EmS-No. : F-E / S-E  
Special provisions : LQ 5 I · E 1  
Hazard label(s) : 3

### Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3  
Special provisions : E 1  
Hazard label(s) : 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

Land transport (ADR/RID) : No  
Sea transport (IMDG) : No  
Air transport (ICAO-TI / IATA-DGR) : No

### 14.6 Special precautions for user

None

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3, 30, 40

##### Other regulations (EU)

##### Restrictions of use in accordance with regulation (EC) 2019/1148 on the marketing and use of explosives precursors

None

##### Labelling for contents according to regulation (EC) No. 648/2004

aromatic hydrocarbons 15 - < 30 %

#### National regulations

##### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

##### Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

##### Water hazard class (WGK)

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

### 15.2 Chemical safety assessment

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-101-6  
Universal thinner normal

Revision date : 09.11.2021

Print date : 10.11.2021

Version (Revision) : 8.0.0 (7.0.0)

For this substance / mixture a chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### 16.1 Indication of changes

03. Hazardous ingredients · 08. Occupational exposure limit values

#### 16.2 Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
AGW = Occupational Exposure Limits  
ATE = Acute Toxicity Estimates  
AwSV = Ordinance on facilities for the handling of substances hazardous to water  
DMEL = Derived Minimal Effect Levels  
DNEL = Derived No Effect Level  
EC<sub>x</sub> = effective concentration  
H (8.1) = skin resorptive / risk of skin absorption  
IATA = International Air Transport Association  
ICAO = International Civil Aviation Organization  
IMDG = International Maritime Code for Dangerous Goods  
LC<sub>x</sub>/LD<sub>x</sub>/LL<sub>x</sub> = Lethal Concentration/Dose/Loading for x % of a population of test organisms  
MARPOL = International Convention for the Prevention of Marine Pollution from Ships  
NOAEC/NOAEL = No Observed Adverse Effect Concentration/Level  
NOEC/NOEL = No Observed Effect Concentration/Level  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, bioaccumulative and toxic  
PNEC = Predicted No Effect Concentration  
RID = Règlement concernant le transport international ferroviaire des marchandises dangereuses  
RCP = reciprocal calculation procedure  
S(a/h/ah) (8.1) = risk of sensitisation (of the respiratory tract/of the skin/of the respiratory tract and the skin)  
SVHC = Substances of Very high Concern  
STEL = Short-Time-Exposure Limit  
TRGS = Technical rules for hazardous substances  
TWA = Time Weighted Average  
VOC = volatile organic compounds  
vPvB = very persistent and very bioaccumulative  
VwVwS = Administrative regulation of substances hazardous to water  
WGK = water hazard class acc. ordinance on facilities for handling substances that are hazardous to water (AwSV)  
Y (8.1) = No risk of fetal damage will have to be feared, if the occupational exposure limit values (AGW) and the biological limit values (BGW) are observed.  
Z (8.1) = The risk of fetal damage must be feared, even if the occupational exposure limit values (AGW) and the biological limit values (BGW) are observed.

#### 16.3 Key literature references and sources for data

None

#### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The classification for health hazards, physicochemical hazards and environmental hazards were derived from a combination of calculation methods and, if available, test data.

#### 16.5 Relevant H- and EUH-phrases (Number and full text)

|      |   |
|------|---|
| H225 | Highly flammable liquid and vapour.           |
| H226 | Flammable liquid and vapour.                  |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin.                 |
| H315 | Causes skin irritation.                       |
| H319 | Causes serious eye irritation.                |
| H332 | Harmful if inhaled.                           |
| H335 | May cause respiratory irritation.             |
| H336 | May cause drowsiness or dizziness.            |

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

|                        |   |                             |               |
|------------------------|---|-----------------------------|---------------|
| <b>Trade name :</b>    | SWIN 60-101-6<br>Universal thinner normal | <b>Version (Revision) :</b> | 8.0.0 (7.0.0) |
| <b>Revision date :</b> | 09.11.2021                                |                             |               |
| <b>Print date :</b>    | 10.11.2021                                |                             |               |

---

|       |  |
|-------|--|
| H360D | May damage the unborn child.                                       |
| H373  | May cause damage to organs through prolonged or repeated exposure. |

### 16.6 Training advice

None

### 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---