

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SWIN 70-101-6
degreaser (34612)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Washing and cleaning products (including solvent based products)

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

SWIN Lacksysteme
Inh. Ludwig Schöne e.K

Street : Boschweg 5

Postal code/city : D-48351 Everswinkel

Telephone : +49(0)2582/67613

Telefax : +49(0)258267677

Information contact : info@swinsysteme.de

1.4 Emergency telephone number

Tel: +49 (0) 30 / 19 24 0 Giftzentrale Berlin

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Flam. Liq. 2 ; H225 - Flammable liquids : Category 2 ; Highly flammable liquid and vapour.

Repr. 2 ; H361d - Reproductive toxicity : Category 2 ; Suspected of damaging the unborn child.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

XYLENE ; CAS No. : 1330-20-7
TOLUENE ; CAS No. : 108-88-3

Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P331 Do NOT induce vomiting.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container to disposal.

Additional information

P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3 Other hazards

Results of PBT and vPvB assessment :
PBT: No data available
vPvB: No data available

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; REACH registration No. : 01-2119473851-33 ; EC No. : 920-750-0; CAS No. : 64742-49-0

Weight fraction : $\geq 50 - < 100$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

XYLENE ; REACH registration No. : 01-2119488216-32 ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction : $\geq 20 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335

TOLUENE ; REACH registration No. : 01-2119471310-51 ; EC No. : 203-625-9; CAS No. : 108-88-3

Weight fraction : $\geq 20 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 Repr. 2 ; H361d STOT RE 2 ; H373 Skin Irrit. 2 ; H315 STOT SE 3 ; H336

PROPAN-2-OL ; REACH registration No. : 01-2119457558-25 ; EC No. : 200-661-7; CAS No. : 67-63-0

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

Additional information

Full text of H- and EUH-phrases: see section 16.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove affected person from the danger area and lay down. Observe risk of aspiration if vomiting occurs. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

Following inhalation

Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Provide fresh air.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness Headache Nausea Impairment of vision Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO₂) Water spray

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic Carbon monoxide Carbon dioxide (CO₂)

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

For non-emergency personnel

Use personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

For emergency responders

Use appropriate respiratory protection. Remove persons to safety. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.2 Environmental precautions

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

6.4 Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment (refer to section 8). Avoid: generation/formation of aerosols

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists
Skin contact
Eye contact
Take precautionary measures against static discharges.

Measures to prevent fire

Keep away from sources of ignition. - No smoking. Usual measures for fire prevention. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only antistatically equipped (spark-free) tools. Wear anti-static footwear and clothing
Take precautionary measures against static discharges.

Measures to prevent aerosol and dust generation

Vapours/aerosols must be exhausted directly at the point of origin. Use only in well-ventilated areas.

Environmental precautions

Shafts and sewers must be protected from entry of the product.

7.2 Conditions for safe storage, including any incompatibilities

Hints on joint storage

Storage class (TRGS 510) : 3

Further information on storage conditions

Keep container tightly closed. Keep/Store only in original container.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 1200 mg/m³

Version :

XYLENE ; CAS No. : 1330-20-7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 440 mg/m³
Peak limitation : 2(II)
Remark : H
Version : 04.11.2017
Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 442 mg/m³
Remark : H
Version : 08.06.2000
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 221 mg/m³
Remark : H
Version : 08.06.2000

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 190 mg/m³
Peak limitation : 4(II)
Remark : H, Y
Version : 04.11.2017
Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 384 mg/m³
Remark : H
Version : 07.02.2006
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 192 mg/m³
Remark : H
Version : 07.02.2006

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 200 ppm / 500 mg/m³
Peak limitation : 2(II)
Remark : Y
Version : 04.11.2017

Biological limit values

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Xylene / Whole blood (B) / End of exposure or end of shift
Limit value : 1,5 mg/l
Version : 31.03.2004
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Methylhippuric acid / Urine (U) / End of exposure or end of shift
Limit value : 2 g/l
Version : 31.03.2004

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Toluene / Whole blood (B) / End of exposure or end of shift
Limit value : 1 mg/l
Version : 31.03.2004
Limit value type (country of origin) : TRGS 903 (D)
Parameter : o-Cresol / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts
Limit value : 3 mg/l
Version : 31.03.2004

PROPAN-2-OL ; CAS No. : 67-63-0

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6

degreaser

Revision date : 15.08.2017

Version (Revision) :

3.0.0 (2.0.0)

Print date : 15.08.2017

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Acetone / Whole blood (B) / End of exposure or end of shift

Limit value : 50 mg/l

Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Acetone / Urine (U) / End of exposure or end of shift

Limit value : 50 mg/l

Version : 31.03.2004

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL/DMEL (Industrial) (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0)

Exposure route : Dermal

Limit value : 773 mg/kg

Safety factor : 24 h

Limit value type : DNEL/DMEL (Industrial) (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0)

Exposure route : Inhalation

Exposure frequency : Long-term (repeated)

Limit value : 2035 mg/m³

Safety factor : 8 h

Limit value type : DNEL worker (local) (XYLENE ; CAS No. : 1330-20-7)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 289 mg/m³

Limit value type : DNEL worker (systemic) (XYLENE ; CAS No. : 1330-20-7)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 289 mg/m³

Limit value type : DNEL worker (systemic) (XYLENE ; CAS No. : 1330-20-7)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 77 mg/m³

Limit value type : DNEL worker (systemic) (XYLENE ; CAS No. : 1330-20-7)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 180 mg/kg

Limit value type : DNEL worker (local) (TOLUENE ; CAS No. : 108-88-3)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 384 mg/m³

Limit value type : DNEL worker (local) (TOLUENE ; CAS No. : 108-88-3)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 192 mg/m³

Limit value type : DNEL worker (systemic) (TOLUENE ; CAS No. : 108-88-3)

Exposure route : Dermal

Exposure frequency : Long-term

Limit value : 384 mg/kg

Limit value type : DNEL worker (systemic) (TOLUENE ; CAS No. : 108-88-3)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 384 mg/m³

Limit value type : DNEL worker (systemic) (TOLUENE ; CAS No. : 108-88-3)

Exposure route : Inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

Exposure frequency : Long-term
Limit value : 192 mg/m³
Limit value type : DNEL worker (systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Dermal
Limit value : 888 mg/kg
Limit value type : DNEL worker (systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Inhalation
Limit value : 500 mg/m³

PNEC

Limit value type : PNEC aquatic, freshwater (XYLENE ; CAS No. : 1330-20-7)
Limit value : 0,327 mg/l
Limit value type : PNEC aquatic, marine water (XYLENE ; CAS No. : 1330-20-7)
Limit value : 0,327 mg/l
Limit value type : PNEC sediment, freshwater (XYLENE ; CAS No. : 1330-20-7)
Limit value : 12,46 mg/kg
Limit value type : PNEC sediment, marine water (XYLENE ; CAS No. : 1330-20-7)
Limit value : 12,46 mg/kg
Limit value type : PNEC sewage treatment plant (STP) (XYLENE ; CAS No. : 1330-20-7)
Limit value : 6,58 mg/l
Limit value type : PNEC aquatic, freshwater (TOLUENE ; CAS No. : 108-88-3)
Limit value : 0,68 mg/l
Limit value type : PNEC aquatic, marine water (TOLUENE ; CAS No. : 108-88-3)
Limit value : 0,68 mg/l
Limit value type : PNEC sediment, freshwater (TOLUENE ; CAS No. : 108-88-3)
Limit value : 16,39 mg/kg
Limit value type : PNEC sediment, marine water (TOLUENE ; CAS No. : 108-88-3)
Limit value : 16,39 mg/kg
Limit value type : PNEC sewage treatment plant (STP) (TOLUENE ; CAS No. : 108-88-3)
Limit value : 13,61 mg/l
Limit value type : PNEC aquatic, freshwater (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 140,9 mg/l
Limit value type : PNEC aquatic, marine water (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 140,9 mg/l
Limit value type : PNEC sediment, freshwater (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 552 mg/kg
Limit value type : PNEC sediment, marine water (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 552 mg/kg

8.2 Exposure controls



Personal protection equipment

Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable material : Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,7 mm

Breakthrough time (maximum wearing time) : 480 min

Recommended glove articles DIN EN 374

Remark : Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. The quality of the protective gloves resistant to chemicals must be chosen

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Overall

Suitable protective clothing : For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes). Chemical resistant safety shoes Only wear fitting, comfortable and clean protective clothing.

Required properties : antistatic. flame-resistant heat-resistant

Respiratory protection

Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values aerosol or mist formation. spray application

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter:

Filter type: A

General health and safety measures

Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Odour : characteristic

Appearance

Colour : colourless

Odour threshold

No data available

Safety relevant basis data

| | | | |
|--|--------------|-------------------------|------------------|
| Melting point/melting range : | | No data available | |
| Initial boiling point and boiling range : | (1013 hPa) | 82 - 143 °C | |
| Decomposition temperature : | | No data available | |
| Flash point : | | -2 °C | DIN 51755 part 1 |
| Ignition temperature : | | 425 °C | DIN 51794 |
| Lower explosion limit : | | 0,8 Vol-% | |
| Upper explosion limit : | | 7 Vol-% | |
| Vapour pressure : | (20 °C) | 29 hPa | |
| Density : | (20 °C) | 0,783 g/cm ³ | DIN 51757 |
| Water solubility : | (20 °C) | partially miscible | |
| pH-value: | (20 °C) | not applicable | |
| log P O/W : | | No data available | |
| Cinematic viscosity : | (40 °C) | No data available | |
| Relative vapour density : | (20 °C) | No data available | |
| Vapourisation rate : | | No data available | |
| Maximum VOC content (EC) : | | 100 Wt % | 1999/13/EC |
| VOC-value : | | 783 g/l | 2004/42/EC |
| Oxidising liquids : | | No data available. | |
| Explosive properties : | | Not determined. | |

9.2 Other information

None

SECTION 10: Stability and reactivity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Exothermic reaction with:
Alkali (lye). Acid Oxidising agent, strong.

10.6 Hazardous decomposition products

Gases/vapours, combustible

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

| | |
|------------------|---------------------------------------|
| Parameter : | ATEmix calculated |
| Exposure route : | Oral |
| Effective dose : | not relevant |
| Parameter : | LD50 (TOLUENE ; CAS No. : 108-88-3) |
| Exposure route : | Oral |
| Species : | Rat |
| Effective dose : | > 5000 mg/kg |

STOT-single exposure

See section 2

Acute dermal toxicity

| | |
|------------------|---------------------------------------|
| Parameter : | ATEmix calculated |
| Exposure route : | Dermal |
| Effective dose : | 4944 mg/kg |
| Parameter : | LD50 (TOLUENE ; CAS No. : 108-88-3) |
| Exposure route : | Dermal |
| Species : | Rabbit |
| Effective dose : | > 5000 mg/kg |
| Parameter : | ATE (XYLENE ; CAS No. : 1330-20-7) |
| Exposure route : | Dermal |
| Effective dose : | 1100 mg/kg |

Acute inhalation toxicity

| | |
|------------------|---------------------------------------|
| Parameter : | ATEmix calculated |
| Exposure route : | Inhalative (vapour) |
| Effective dose : | 49,4 mg/l |
| Parameter : | LC50 (TOLUENE ; CAS No. : 108-88-3) |
| Exposure route : | Inhalation |
| Species : | Rat |
| Effective dose : | > 20 mg/l |
| Exposure time : | 4 h |

Irritant and corrosive effects

See section 2

Sensitisation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

See section 2

Repeated dose toxicity (subacute, subchronic, chronic)

Subacute oral toxicity

STOT-repeated exposure

See section 2

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

See section 2

Germ cell mutagenicity

See section 2

Reproductive toxicity

See section 2

Aspiration hazard

See section 2

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : > 13,4 mg/l
Exposure time : 96 h
Parameter : LC50 (TOLUENE ; CAS No. : 108-88-3)
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 66 mg/l
Exposure time : 96 h
Parameter : LC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 9640 mg/l
Exposure time : 96 h

Chronic (long-term) fish toxicity

Parameter : Chronic (long-term) fish toxicity (XYLENE ; CAS No. : 1330-20-7)
Species : Oncorhynchus mykiss (Rainbow trout)
Effective dose : > 1,3 mg/l
Exposure time : 56 Day(s)

Acute (short-term) daphnia toxicity

Parameter : EC50 (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0)
Species : Daphnia magna (Big water flea)
Effective dose : 3 mg/l
Exposure time : 48 h
Parameter : EC50 (TOLUENE ; CAS No. : 108-88-3)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 270 mg/l
Exposure time : 24 h
Parameter : EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 9714 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

Exposure time : 24 h

Acute (short-term) algae toxicity

Parameter : EC50 (TOLUENE ; CAS No. : 108-88-3)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 125 - 160 mg/l
Exposure time : 48 h
Parameter : EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 100 mg/l
Exposure time : 72 h

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

14.1 UN number

UN 1263

14.2 UN proper shipping name

Land transport (ADR/RID)

PAINT RELATED MATERIAL

Sea transport (IMDG)

PAINT RELATED MATERIAL (NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

Air transport (ICAO-TI / IATA-DGR)

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 33
Tunnel restriction code : D/E
Special provisions : 640D · LQ 5 I · E 2
Hazard label(s) : 3 / N

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser
Revision date : 15.08.2017
Print date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / ~~S-E~~
Special provisions : LQ 51 · E 2
Hazard label(s) : 3 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 2
Hazard label(s) : 3

14.4 Packing group

II

14.5 Environmental hazards

Land transport (ADR/RID) : Yes
Sea transport (IMDG) : Yes (P)
Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : 20 - 25 %

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Sea transport (IMDG) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG) · 14. Transport hazard class(es) - Air transport (ICAO-TI / IATA-DGR)

16.2 Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
AGW = Arbeitsplatzgrenzwert
ATE = Acute Toxicity Estimates
DMEL = Derived Minimal Effect Levels
DNEL = Derived No Effect Level
H (8.2) = hautresorptiv (= absorbable through skin contact)
IATA = International Air Transport Association
IMDG = International Maritime Code for Dangerous Goods
LC = Letalkonzentration

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 70-101-6
degreaser

Revision date : 15.08.2017

Version (Revision) : 3.0.0 (2.0.0)

Print date : 15.08.2017

LD50 = Lethal Dose, 50%

MAK = Maximale Arbeitsplatzkonzentration

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

PBT = Persistent, bioaccumulative and toxic

PNEC = Predicted No Effect Concentration

RID = Règlement concernant le transport international ferroviaire des marchandises dangereuses

RCP = reciprocal calculation procedure

SVHC = Substances of Very high Concern

STEL = Short-Time-Exposure Limit

TWA = Time Weighted Average (= Zeitgewichteter Durchschnittsgrenzwert für Exposition)

VOC = volatile organic compounds

vPvB = very persistent and very bioaccumulative

VwVwS = Verwaltungsvorschrift wassergefährdender Stoffe

WGK = Wassergefährdungsklasse gem. Verwaltungsvorschrift wassergefährdender Stoffe-VwVwS Y (8.2) = Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet werden

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

16.5 Relevant H- and EUH-phrases (Number and full text)

| | |
|-------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
