

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdüner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

7798 Uni-Verdüner (231)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Metal surface treatment products, including galvanic and electroplating products Washing and cleaning products (including solvent based products)

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

SWIN Lacksysteme

Street : Boschweg 5

Postal code/city : D-48351 Everswinkel

Telephone : +49 (0) 25 82 / 67 61 3

Telefax : +49 (0) 25 82 / 67 67 7

Information contact : info@swin.de

1.4 Emergency telephone number

Tel: +49(0) 30 / 19 24 0 Giftzentrale Berlin

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Category 3 ; Harmful to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Flam. Liq. 2 ; H225 - Flammable liquids : Category 2 ; Highly flammable liquid and vapour.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

N-BUTYL ACETATE ; CAS No. : 123-86-4

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0

2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1

BUTAN-1-OL ; CAS No. : 71-36-3

Hazard statements

H225 Highly flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

H304 May be fatal if swallowed and enters airways.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P310 Immediately call a POISON CENTER/doctor
P321 Specific treatment
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

2.3 Other hazards

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Hazardous ingredients

N-BUTYL ACETATE ; REACH registration No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4

Weight fraction : $\geq 20 - < 25$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

ETHYL ACETATE ; REACH registration No. : 01-2119475103-46 ; EC No. : 205-500-4; CAS No. : 141-78-6

Weight fraction : $\geq 10 - < 20$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

ACETONE ; REACH registration No. : 01-2119471330-49 ; EC No. : 200-662-2; CAS No. : 67-64-1

Weight fraction : $\geq 10 - < 20$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

XYLENE ; REACH registration No. : 01-2119488216-32 ; EC No. : 215-535-7; CAS No. : 1330-20-7

Weight fraction : $\geq 10 - < 12,5$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; REACH registration No. : 01-2119475514-35 ; EC No. : 921-024-6; CAS No. : 64742-49-0

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 Skin Irrit. 2 ; H315 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

PROPAN-2-OL ; REACH registration No. : 01-2119457558-25 ; EC No. : 200-661-7; CAS No. : 67-63-0

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

1-METHOXY-2-PROPANOL ; REACH registration No. : 01-2119457435-35 ; EC No. : 203-539-1; CAS No. : 107-98-2

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336

2-METHYLPROPAN-1-OL ; REACH registration No. : 01-2119484609-23 ; EC No. : 201-148-0; CAS No. : 78-83-1

Weight fraction : $\geq 3 - < 5$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 STOT SE 3 ; H336

BUTAN-1-OL ; EC No. : 200-751-6; CAS No. : 71-36-3

Weight fraction : $\geq 3 - < 5$ %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 STOT SE 3 ; H336

2-METHOXY-1-METHYLETHYL ACETATE ; REACH registration No. : 01-2119475791-29 ; EC No. : 203-603-9; CAS No. : 108-

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

65-6

Weight fraction : $\geq 0,5 - < 5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226
Substance with a common (EC) occupational exposure limit value.

TOLUENE ; REACH registration No. : 01-2119471310-51 ; EC No. : 203-625-9; CAS No. : 108-88-3

Weight fraction : $\geq 1 - < 3 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Asp. Tox. 1 ; H304 Repr. 2 ; H361d STOT RE 2 ; H373 Skin Irrit. 2 ; H315 STOT SE 3 ; H336

Hydrocarbons, C9, aromates ; REACH registration No. : 01-2119455851-35 ; EC No. : 918-668-5; CAS No. : 64742-95-6

Weight fraction : $\geq 0,5 - < 2,5 \%$
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336
Aquatic Chronic 2 ; H411

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove contaminated, saturated clothing immediately.

Following inhalation

Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Provide fresh air.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO₂) Water spray Unsuitable extinguishing media Full water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

6.1 Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4 Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

SECTION 7: Handling and storage

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

7.1 Precautions for safe handling

Wear personal protection equipment (refer to section 8). Avoid: Generation/formation of aerosols It is recommended to design all work processes always so that the following is excluded: Inhalation Skin contact Eye contact

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions

Keep container tightly closed. Keep/Store only in original container.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 62 ppm / 300 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 02.04.2014

ETHYL ACETATE ; CAS No. : 141-78-6

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 400 ppm / 1500 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 02.04.2014

ACETONE ; CAS No. : 67-64-1

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 500 ppm / 1200 mg/m³

Peak limitation : 2(I)

Version : 02.04.2014

Limit value type (country of origin) : TWA (EC)

Limit value : 500 ppm / 1210 mg/m³

Version : 08.06.2000

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 100 ppm / 440 mg/m³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdüner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

Peak limitation : 2(II)
Remark : H
Version : 02.04.2014

Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 442 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 221 mg/m³
Remark : H
Version : 08.06.2000

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ; CAS No. : 64742-49-0
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 1500 mg/m³
Version :

PROPAN-2-OL ; CAS No. : 67-63-0
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 200 ppm / 500 mg/m³
Peak limitation : 2(II)
Remark : Y
Version : 02.04.2014

1-METHOXY-2-PROPANOL ; CAS No. : 107-98-2
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 370 mg/m³
Peak limitation : 2(I)
Remark : Y
Version : 02.04.2014

Limit value type (country of origin) : STEL (EC)
Limit value : 150 ppm / 568 mg/m³
Remark : H
Version : 08.06.2000

Limit value type (country of origin) : TWA (EC)
Limit value : 100 ppm / 375 mg/m³
Remark : H
Version : 08.06.2000

2-METHYLPROPAN-1-OL ; CAS No. : 78-83-1
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 310 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 02.04.2014

BUTAN-1-OL ; CAS No. : 71-36-3
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 100 ppm / 310 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 02.04.2014

2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6
Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 270 mg/m³
Peak limitation : 1(I)
Remark : Y
Version : 02.04.2014

Limit value type (country of origin) : STEL (EC)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

Limit value : 100 ppm / 550 mg/m³
Remark : H
Version : 08.06.2000
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 275 mg/m³
Remark : H
Version : 08.06.2000

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 50 ppm / 190 mg/m³
Peak limitation : 4(II)
Remark : H, Y
Version : 02.04.2014
Limit value type (country of origin) : STEL (EC)
Limit value : 100 ppm / 384 mg/m³
Remark : H
Version : 07.02.2006
Limit value type (country of origin) : TWA (EC)
Limit value : 50 ppm / 192 mg/m³
Remark : H
Version : 07.02.2006

Biological limit values

ACETONE ; CAS No. : 67-64-1

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Urine (U) / End of exposure or end of shift
Limit value : 80 mg/l
Version : 31.03.2004

XYLENE ; CAS No. : 1330-20-7

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Xylene / Whole blood (B) / End of exposure or end of shift
Limit value : 1,5 mg/l
Version : 31.03.2004
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Methylhippuric acid / Urine (U) / End of exposure or end of shift
Limit value : 2 g/l
Version : 31.03.2004

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Whole blood (B) / End of exposure or end of shift
Limit value : 50 mg/l
Version : 31.03.2004
Limit value type (country of origin) : TRGS 903 (D)
Parameter : Acetone / Urine (U) / End of exposure or end of shift
Limit value : 50 mg/l
Version : 31.03.2004

BUTAN-1-OL ; CAS No. : 71-36-3

Limit value type (country of origin) : TRGS 903 (D)
Parameter : 1-Butanol / Urine (U) / Before next shift
Limit value : 2 mg/g Kr
Version : 31.03.2004
Limit value type (country of origin) : TRGS 903 (D)
Parameter : 1-Butanol / Urine (U) / End of exposure or end of shift
Limit value : 10 mg/g Kr
Version : 31.03.2004

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

TOLUENE ; CAS No. : 108-88-3

Limit value type (country of origin) : TRGS 903 (D)

Parameter : Toluene / Whole blood (B) / End of exposure or end of shift

Limit value : 1 mg/l

Version : 31.03.2004

Limit value type (country of origin) : TRGS 903 (D)

Parameter : o-Cresol / Urine (U) / End of exposure or end of shift ; At long term exposure: after several previous shifts

Limit value : 3 mg/l

Version : 31.03.2004

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Eye glasses with side protection

Face protection shield

Skin protection

Tested protective gloves must be worn

Hand protection

Suitable material : Recommended glove articles DIN EN 374

Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0,7 mm

Breakthrough time (maximum wearing time) $30 < x < 60$ min.

Remark : Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection

Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Respiratory protection necessary at: exceeding exposure limit values aerosol or mist formation. spray application

Suitable respiratory protection apparatus

Filter type: AX (for group 2 low boilers). In case of a maximum contaminant concentration in inhaled air of 1000 mL/m³ (0.1 % by vol.), group 2 may be used for a maximum of 60 min. In case of a maximum contaminant concentration in inhaled air of 5000 mL/m³ (0.5 % by vol.), group 2 may be used for a maximum of 20 min.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Appearance

Colour : colourless

Odour

characteristic

Odour threshold

No data available

Safety relevant basis data

Initial boiling point and boiling range : (1013 hPa)

56 - 175 °C

Flash point :

-18 °C

DIN 51755 part 1

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

Ignition temperature :	295 °C	DIN 51794
Lower explosion limit :	1 Vol-%	
Upper explosion limit :	44 Vol-%	
Vapour pressure :	247 hPa	
Density : (20 °C)	0,845 g/cm ³	DIN 51757
pH-value: (20 °C)	n.a.	
Maximum VOC content (EC) :	100 Wt %	

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

No information available.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Exothermic reaction with:
Alkali (lye). Acid Oxidising agent, strong.

10.6 Hazardous decomposition products

Carbon monoxide.
Carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	16667 mg/kg
Parameter :	ATE (BUTAN-1-OL ; CAS No. : 71-36-3)
Exposure route :	Oral
Effective dose :	500 mg/kg

Acute dermal toxicity

Parameter :	ATEmix calculated
Exposure route :	Dermal
Effective dose :	9167 mg/kg
Parameter :	ATE (XYLENE ; CAS No. : 1330-20-7)
Exposure route :	Dermal
Effective dose :	1100 mg/kg

Acute inhalation toxicity

Parameter :	ATEmix calculated
Exposure route :	Inhalative (vapour)
Effective dose :	91,7 mg/l

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdüner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

13.2 Additional information

Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (N-BUTYL ACETATE · NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (N-BUTYL ACETATE · NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (N-BUTYL ACETATE · NAPHTHA (PETROLEUM), HYDROTREATED LIGHT)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 33
Tunnel restriction code : D/E
Special provisions : 640D · LQ 4 · LQ 1 I · E 2
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 1 I · E 2
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

Hazard label(s) : 3

14.4 Packing group

II

14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Relevant H- and EUH-phrases (Number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : 7798 Uni-Verdünner
Revision date : 11.06.2015
Print date : 31.08.2015

Version : 1.0.0

16.5 Training advice

None

16.6 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
