

Version number 3

Revision: 15.05.2023

1 Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier CODE 3003 · Trade name: SWIN REAKTIONSVERDÜNNER NORMAL • Article number: 30-101-X 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Product category PC9a Coatings and paints, thinners, paint removers · Process category PROC7 Industrial spraying PROC11 Non industrial spraying • Environmental release category ERC8c Widespread use leading to inclusion into/onto article (indoor) · Application of the substance / the mixture Coating material · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: SWIN Lacksysteme Boschweg 5 D-48351 Everswinkel info@swinsysteme.de • Further information obtainable from: +49 2582-67613 / +49 2582-67677 · 1.4 Emergency telephone number: Giftinformationszentrum Göttingen (GIZ-Nord) Phone: +49 (0)551-19240 2 Hazards identification · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. corrosion Met. Corr.1 H290 May be corrosive to metals. Eve Dam. 1 H318 Causes serious eye damage. Harmful if swallowed. Acute Tox. 4 H302 Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS02 GHS05 GHS07 · Signal word Danger

(Contd. on page 2)



Version number 3

Revision: 15.05.2023

Trade name: SWIN REAKTIONSVERDÜNNER NORMAL

	(Contd. of page 1)
• Hazard st	
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335-H3.	36 May cause respiratory irritation. May cause drowsiness or dizziness.
· Precautio	nary statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P305+P3	51+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P330	Rinse mouth.
P362+P3	64 Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
• 2.3 Other	hazards -
· Results of	f PBT and vPvB assessment

• *PBT*: Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 71-36-3	butan-1-ol	50-100%
EINECS: 200-751-6	🚸 Flam. Liq. 3, H226; 🔶 Eye Dam. 1, H318; 🚸 Acute Tox.	
Reg.nr.: 01-2119484630-38-XXXX	4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 7664-38-2	phosphoric acid	<i>≤</i> 2.5%
EINECS: 231-633-2	Skin Corr. 1B, H314	
Reg.nr.: 01-2119752438-31-XXXX		
0	- dive of the listed has made have a sefer to continue 16	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

• 4.1 Description of first aid measures

· General information: Personal protection for the First Aider.

- After inhalation:
- Supply fresh air.

Seek medical treatment in case of complaints.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

- *If skin irritation continues, consult a doctor.*
- After eye contact:

Rinse opened eye for several minutes under running water.

Seek medical treatment.

• *After swallowing:* Do not induce vomiting; call for medical help immediately.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Version number 3

Revision: 15.05.2023

Trade name: SWIN REAKTIONSVERDÜNNER NORMAL

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

7 Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Restrict the quantity stored at the work place.

Information about fire - and explosion protection: Fumes can combine with air to form an explosive mixture. Flammable gas-air mixtures may form in empty receptacles. Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities • Storage:
- *Requirements to be met by storerooms and receptacles:* Unsuitable material for receptacle: steel. Provide solvent resistant, sealed floor.
- Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions).
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 4)

GB



Version number 3

Revision: 15.05.2023

Trade name: SWIN REAKTIONSVERDÜNNER NORMAL

 WEL Short-term value: 154 mg/m³, 50 ppm Sk Schort-term value: 2 mg/m³ Long-term value: 1 mg/m³ Additional information: The lists valid during the making were used as basis. S1 Exposure controls Personal protective equipment: General protective and hyginci measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. 4void contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu use sulf-contained respiratory protective device. Filter A2P2 Protective gloves Protective gloves with CE-labelling of category III. Waterial of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances. It resistance of the glove material can not be exactly calculated in advance and has therefore to be check storic to the application. 4 sy rotection from splashes gloves made of the following materials are suitable: Nirile rubber (Ansell Soi-Vex®) Freeterion time of glove material: ≥ 0.4 mm Penetration time of glove material: ≥ 0.4 mm Penetration time of glove material: Wate for the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eve protection: Every clochin: Protective clobhing, anti-static (TYYEK® CLASSIC PLUS) Safety shoex/boots, antstatic 	-	lients with limit values that require monitoring at the workplace: 3 butan-1-ol
 WEL Short-term value: 2 mg/m³ Long-term value: 1 mg/m³ Additional information: The lists valid during the making were used as basis. A Exposure controls Personal protective equipment: General protective equipment: General protective equipment: Mathids before breaks and at the end of work. Do not inhale gases / fitmes / aerosols. Avoid contact with the eyes and skin. Respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu se self-contained respiratory protective device. Filter A2/P2 Protective gloves with CE-labelling of category III. Waterial of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies form manufacturer to manufacturer. As the product is a preparation of several substances, to septication. s protection manufacture ration can not be exactly calculated in advance and has therefore to be		° 11
 WEL Short-term value: 2 mg/m³ Long-term value: 1 mg/m³ Additional information: The lists valid during the making were used as basis. A Exposure controls Personal protective equipment: General protective equipment: General protective equipment: Mathids before breaks and at the end of work. Do not inhale gases / fitmes / aerosols. Avoid contact with the eyes and skin. Respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu se self-contained respiratory protective device. Filter A2/P2 Protective gloves with CE-labelling of category III. Waterial of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies form manufacturer to manufacturer. As the product is a preparation of several substances, to septication. s protection manufacture ration can not be exactly calculated in advance and has therefore to be	7664	38-2 phosphoric acid
Long-term value: $I mg/m^3$ Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / finuse / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable gases / finuse / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu use self-contained respiratory protective device. Filter A2/P? Protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, t resistance of the glove material can not be exactly calculated in advance and has therefore to be check rior to the application. As protection fine splashes gloves made of the following materials are suitable: Nitrie rubber (Ansell Sol-Ferse) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact $\Rightarrow 480$ minutes gloves made of the following materials are suitable: HPE-laminate time (Ansell Barrier®) Exerction: The heretotion: For the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact $\Rightarrow 480$ minutes gloves made of the following materials a		
A 2 Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / junes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposus ise self-contained respiratory protective device. Filter A2/P2 Protection of hands: Duly use chemical-protective gloves with CE-labelling of category III. WW Protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, to resistance of the glove material can not be exactly calculated in advance and has therefore to be check prior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of USM Recommended thickness of Lew 4 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to sherved. For the permaent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Ever protection: They have also age goggles For the cont break through time has to be found out by the manufacturer of the protective gloves and has to sherved. For the permaent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminate film (A		
Personal protective equipment: General protective equipment: General protective and hygenic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / junes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu use self-contained respiratory protective device. Filter A2.02 Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. Protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is a preparation of several substances, to revisit a form manufacturer to manufacturer. As the product is a preparation of several substances, to revisitance of the glove material can not be exactly calculated in advance and has therefore to be check storic to the application. As protection from splashes gloves made of the following materials are suitable: Nirrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Preteration time of glove material Level 4 I The permanent contact => 480 minutes gloves made of the following materials are suitable: HPFE-laminate film (Ansell Barrier®) Ever protection: Tightly sealed goggles Protection: Protection clowing, anti-static (TYVEK® CLASSIC PLUS)	Additi	onal information: The lists valid during the making were used as basis.
Personal protective equipment: General protective equipment: General protective and hygenic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / junes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposus use self-contained respiratory protective device. With * A1P2 Protection of hands: Duly use chemical-protective gloves with CE-labelling of category III. Will was chemical-protective gloves with CE-labelling of category III. Will a start of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is a preparation of several substances, to resistance of the glove material can not be exactly calculated in advance and has therefore to be check whore (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Preteration from splashes gloves made of the following materials are suitable: Nirrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Preteration time of glove material Level 4 I The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permaent contact $\Rightarrow 480$ minutes gloves made of the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Ever protection: Tightly sealed goggles Material: Protective closhing, anti-static (TYVEK® CLASSIC PLUS)	8.2 Ex	posure controls
Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu see self-contained respiratory protective device. Filter A2/P2 Protection of hands: Only use chemical-protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, to revisatione of the gloves material can not be exactly calculated in advance and has therefore to be check ror to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Fecw) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Pales of the permeation: $Level \le 1$ The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: WPE-laminatet film (Ansell Barrier®) Eye protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection: Protection:	Person	nal protective equipment:
Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / Junes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Lie suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu see self-contained respiratory protective device. Filter A2/P2 Protection of hands: Duly use chemical-protective gloves with CE-labelling of category III. Waterial of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, t resistance of the gloves material can not be exactly calculated in advance and has therefore to be check protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Yex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material The selection time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HYPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clohing, anti-static (TYYEK® CLASSIC PLUS)		
Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu use self-contained respiratory protective device. Filter A2/P2 Protection of hands: Duly use chemical-protective gloves with CE-labelling of category III. Work of the suitable gloves with CE-labelling of category III. Protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, to revisitance of the glove material can not be exactly calculated in advance and has therefore to be check prior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration from splashes gloves and out by the manufacturer of the protective gloves and has to observed. For the permention: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu- use self-contained respiratory protective device. Filter A2/P2 Protection of hands: Duly use chemical-protective gloves with CE-labelling of category III. With Protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, to revestive skin protection. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Eye protection: For the permeation: For the perme		
Avoid contact with the eyes and skin. Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposu- use self-contained respiratory protective device. Filter A2/P2 Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. With Protection of thands: Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, t revistance of the glove material can not be exactly calculated in advance and has therefore to be check orior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: $Level \le 1$ The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Experimenter: For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Experimenter: For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Experimenter: For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Experimenter: For the permetion: For the permetion: For the permetion: For the p		
Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure see self-contained respiratory protective device. Filter A2/P2 Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. Image: Contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, trevistance of the glove material can not be exactly calculated in advance and has therefore to be check borior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Pretention time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable:		
Use suitable respiratory protective device in case of insufficient ventilation. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A2/P2 Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. Work of the protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, to resistance of the glove material can not be exactly calculated in advance and has therefore to be check orior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vec®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permeation classer 800 minutes gloves made of the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Eye protection: For the permeation classer 800 minutes gloves made of the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Eye protection: For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Eye protection: For the permanent contact => class flow and the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Eye protection: For the permeation: Level ≤ 1 The vact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminate film (Ansell Barrier®) Eye protection: For		
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A2/P2 Protection of hands: Only use chemical-protective gloves with CE-labelling of category III.		
use self-contained respiratory protective device. Filter A2/P2 Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. We chemical-protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, t resistance of the glove material can not be exactly calculated in advance and has therefore to be check orior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permeation: Level ≤ 1 The permeation time (Ansell Barrier®) Eye protection: We protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Filter A2/P2 Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. Will protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, t resistance of the glove material can not be exactly calculated in advance and has therefore to be check prior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Wightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Protection of hands: Only use chemical-protective gloves with CE-labelling of category III. Image: Protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, t resistance of the glove material can not be exactly calculated in advance and has therefore to be check or ior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permeanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Experimenter Experimenter Tightly sealed goggles Body protection: Protection Protection Protection: Protection: Protection: Protection: Protection: <		
Protective gloves Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be check prior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: $\geq 0.4 \text{ mm}$ Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Preventive skin protection by use of skin-protecting agents is recommended. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of qual and varies from manufacturer to manufacturer. As the product is a preparation of several substances, to resistance of the glove material can not be exactly calculated in advance and has therefore to be check protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)	Only 1	se chemical-protective gloves with CE-labelling of category III.
Material of glovesThe selection of the suitable gloves does not only depend on the material, but also on further marks of qualand varies from manufacturer to manufacturer. As the product is a preparation of several substances, tresistance of the glove material can not be exactly calculated in advance and has therefore to be checkorior to the application.As protection from splashes gloves made of the following materials are suitable:Nitrile rubber (Ansell Sol-Vex®)Recommended thickness of the material: ≥ 0.4 mmPenetration time of glove materialValue for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed.For the permanent contact => 480 minutes gloves made of the following materials are suitable:HPPE-laminatet film (Ansell Barrier®)Eye protection:Tightly sealed gogglesBody protection:Protective clothing, anti-static (TYVEK® CLASSIC PLUS)	Prova	
The selection of the suitable gloves does not only depend on the material, but also on further marks of qual, and varies from manufacturer to manufacturer. As the product is a preparation of several substances, t resistance of the glove material can not be exactly calculated in advance and has therefore to be check brior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
brior to the application. As protection from splashes gloves made of the following materials are suitable: Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: ≥ 0.4 mm Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)	The se and ve	lection of the suitable gloves does not only depend on the material, but also on further marks of qual aries from manufacturer to manufacturer. As the product is a preparation of several substances, t
Nitrile rubber (Ansell Sol-Vex®) Recommended thickness of the material: $\geq 0.4 \text{ mm}$ Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Recommended thickness of the material: $\geq 0.4 \text{ mm}$ Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)	As pro	tection from splashes gloves made of the following materials are suitable:
Penetration time of glove material Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Value for the permeation: Level ≤ 1 The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
The exact break through time has to be found out by the manufacturer of the protective gloves and has to observed. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
bbserved. For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
HPPE-laminatet film (Ansell Barrier®) Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Eye protection: Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Tightly sealed goggles Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Body protection: Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		
Protective clothing, anti-static (TYVEK® CLASSIC PLUS)		Tightly sealed goggles
Protective clothing, anti-static (TYVEK® CLASSIC PLUS)	Rody	- nratection



Version number 3

Revision: 15.05.2023

Trade name: SWIN REAKTIONSVERDÜNNER NORMAL

(Contd. of page 4)

Physical and chemical properties	
9.1 Information on basic physical and cl	hemical properties
• General Information	iemem properties
· Appearance:	
Form:	Fluid
Colour:	Colourless
· Odour:	Alcohol-like
Odour threshold:	Not determined.
pH-value	Not applicable.
Change in condition	
Melting point/freezing point:	-89 °C
Initial boiling point and boiling range:	- 116 °C
Flash point:	23 - 60 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	340 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	9.4 Vol %
Vapour pressure at 20 °C:	6.7 hPa
Vapour pressure:	
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water at 20 °C:	77 g/l
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	24 s (ISO 3 mm)
9.2 Other information	No further relevant information available.

10 Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

GB



Version number 3

Revision: 15.05.2023

Trade name: SWIN REAKTIONSVERDÜNNER NORMAL

(Contd. of page 5)

· Acute toxi	city	toxicological effects
Harmful if		
		want for classification:
71-36-3 bi		700
Oral Dermal	LD50 LD50	790 mg/kg (rat)
		3,400 mg/kg (rabbit)
		8,000 mg/l (rat)
Primary in Skin corre		
	n irritation	
· Serious ey		
	rious eye d	
		e ensitisation Based on available data, the classification criteria are not met. ical information:
		ogenity, mutagenicity and toxicity for reproduction)
· Germ cell	mutagenio	city Based on available data, the classification criteria are not met.
· Carcinoge	nicity Base	ed on available data, the classification criteria are not met.
· Reproduct	tive toxicity	w Based on available data, the classification criteria are not met.
· Reproduct · STOT-sing	tive toxicity gle exposu	y Based on available data, the classification criteria are not met. re
• Reproduct • STOT-sing May cause	t ive toxicity gle exposu e respirator	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness.
 Reproduct STOT-sing May cause STOT-rep 	tive toxicity gle exposu e respirator eated expo	y Based on available data, the classification criteria are not met. re
 Reproduct STOT-sing May cause STOT-rep 	tive toxicity gle exposu e respirator eated expo	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. s ure Based on available data, the classification criteria are not met.
• Reproduct • STOT-sing May cause • STOT-rep • Aspiration	tive toxicity gle exposu e respirator eated expo hazard Ba	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met.
 Reproduct STOT-sing May cause STOT-rep 	tive toxicity gle exposu e respirator eated expo hazard Ba	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met.
• Reproduct • STOT-sing May cause • STOT-rep • Aspiration	tive toxicity gle exposu e respirator eated expo hazard Bo cal inform	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met.
Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to	tive toxicity gle exposu e respiraton eated expo hazard Ba nazard Ba cal inform city city cxicity: No	y Based on available data, the classification criteria are not met. re ry irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available.
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persi 	tive toxicity gle exposu e respirator eated expo hazard Ba nazard Ba cal inform city city: No stence and	y Based on available data, the classification criteria are not met. re ry irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available.
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persit 12.3 Bioac 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ	y Based on available data, the classification criteria are not met. re ry irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available.
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persit 12.3 Bioac 12.4 Mobit 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ lity in soil	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available.
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persit 12.3 Bioac 12.4 Mobit 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ lity in soil l ecologica	y Based on available data, the classification criteria are not met. re ry irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available.
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persi 12.3 Bioac 12.4 Mobi Additional General n 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inforn city exicity: No stence and ccumulativ lity in soil l ecologica otes:	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available.
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persit 12.3 Bioact 12.4 Mobit Additional General n Water haze 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ lity in soil l ecologica otes: ard class 1	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available.
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persit 12.3 Bioact 12.4 Mobit Additional General n Water haze Do not all system. 	tive toxicity gle exposu e respirator eated expo hazard Bo cal inform city exicity: No stence and ccumulativ lity in soil lecologica otes: ard class 1 low undilu	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. f degradability No further relevant information available. re potential No further relevant information available. No further relevant information available. I degradability No further relevant information available. I information: (German Regulation) (Self-assessment): slightly hazardous for water ted product or large quantities of it to reach ground water, water course or sewe
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxid Aquatic to 12.2 Persidies 12.3 Biologic 12.4 Mobidies Additionalies General no Water hazz Do not all system. 12.5 Result 	tive toxicity gle exposu e respirator e ated expo hazard Bo cal inform city exicity: No stence and ccumulativ lity in soil l ecologica otes: ard class 1 low undilu	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available. I information: (German Regulation) (Self-assessment): slightly hazardous for water ted product or large quantities of it to reach ground water, water course or sewa and vPvB assessment
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persi 12.3 Bioac 12.4 Mobi Additional General n Water haz, Do not al. system. 12.5 Result PBT: Not 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ lity in soil decologica otes: ard class 1 low undilu lts of PBT applicable	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available. I information: (German Regulation) (Self-assessment): slightly hazardous for water ted product or large quantities of it to reach ground water, water course or sewa and vPvB assessment
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persi 12.3 Bioac 12.4 Mobi Additional General n Water haze Do not al. system. 12.5 Result PBT: Not vPvB: Not 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ lity in soil lecologica otes: ard class 1 low undilu lts of PBT applicable applicable	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. further relevant information available. further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available. I information: (German Regulation) (Self-assessment): slightly hazardous for water ted product or large quantities of it to reach ground water, water course or sew and vPvB assessment
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persi 12.3 Bioac 12.4 Mobi Additional General n Water haze Do not al. system. 12.5 Result PBT: Not vPvB: Not 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ lity in soil lecologica otes: ard class 1 low undilu lts of PBT applicable applicable	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available. I information: (German Regulation) (Self-assessment): slightly hazardous for water ted product or large quantities of it to reach ground water, water course or sewa and vPvB assessment
 Reproduct STOT-sing May cause STOT-rep Aspiration 2 Ecologic 12.1 Toxic Aquatic to 12.2 Persi 12.3 Bioac 12.4 Mobi Additional General n Water haze Do not al. system. 12.5 Result PBT: Not vPvB: Not 	tive toxicity gle exposu e respirator eated expo hazard Ba cal inform city exicity: No stence and ccumulativ lity in soil lecologica otes: ard class 1 low undilu lits of PBT applicable r adverse e	y Based on available data, the classification criteria are not met. re y irritation. May cause drowsiness or dizziness. sure Based on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. ased on available data, the classification criteria are not met. nation further relevant information available. further relevant information available. degradability No further relevant information available. re potential No further relevant information available. No further relevant information available. I information: (German Regulation) (Self-assessment): slightly hazardous for water ted product or large quantities of it to reach ground water, water course or sewa and vPvB assessment ffects No further relevant information available.

• Uncleaned packaging:

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00: packaging (including separately collected municipal packaging waste)

15 01 10*: packaging containing residues of or contaminated by dangerous substances

(Contd. on page 7) GB



Version number 3

Revision: 15.05.2023

Trade name: SWIN REAKTIONSVERDÜNNER NORMAL

(Contd. of page 6)

• *Recommendation: Disposal must be made according to official regulations.*

14.1 UN-Number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
4DR	1263 PAINT RELATED MATERIAL
IMDG, IATA	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
4DR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
Tuansport outonom	Maximum net quantity per outer packaging: 1000 ml 3
Transport category Tunnel restriction code	5 D/E
IMDG Limited augustities (LO)	5L
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: El
Excepted quantities (EQ)	<i>Code: E1</i> <i>Maximum net quantity per inner packaging: 30 ml</i>
	Maximum net quantity per unter packaging: 50 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 8)

GB



Version number 3

Revision: 15.05.2023

Trade name: SWIN REAKTIONSVERDÜNNER NORMAL

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

- · Information about limitation of use:
- Employment restrictions concerning pregnant and lactating women must be observed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Department issuing SDS: -

· Contact: -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Met. Corr.1: Corrosive to metals - Category 1 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. of page 7)