GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3

Revision: 15.05.2023

1 Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier CODE 3003 · Trade name: SWIN UNIVERSAL EP HÄRTER · Article number: 30-106-\*, 30-108-\* · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Product category PC9a Coatings and paints, thinners, paint removers · Process category PROC7 Industrial spraying PROC11 Non industrial spraying • Environmental release category ERC8c Widespread use leading to inclusion into/onto article (indoor) · Application of the substance / the mixture Hardening agent/ Curing agent · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: SWIN Lacksysteme Boschweg 5 D-48351 Everswinkel info@swinsysteme.de • Further information obtainable from: +49 2582-67613 / +49 2582-67677 · 1.4 Emergency telephone number: Giftinformationszentrum Göttingen (GIZ-Nord) Phone: +49 (0)551-19240 **2 Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. health hazard STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. Asp. Tox. 1 corrosion H318 Causes serious eye damage. Eve Dam. 1 Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. (Contd. on page 2)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 15.05.2023

# Trade name: SWIN UNIVERSAL EP HÄRTER

Unand nict	(Contd. of page 1)
Hazard picto	
J.	
GHS02 C	GHS05 GHS07 GHS08
Signal word	Danger
Hazard-dete	rmining components of labelling:
C18-unsatd.,	branched and linear, tetraethylenepentamine andtriethylenetetramine
xylene	
2,4,6-tris(din	nethylaminomethyl)phenol
butan-1-ol	
	indecamethylenediamine
Hazard state	
	nable liquid and vapour.
	s skin irritation.
	s serious eye damage.
	ause an allergic skin reaction.
	ause respiratory irritation.
	ause damage to organs through prolonged or repeated exposure.
	e fatal if swallowed and enters airways.
	ful to aquatic life with long lasting effects.
	ry statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
P241	smoking. Use explosion-proof [electrical/ventilating/lighting] equipment.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing
1200	protection.
P303 + P361	+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
1 505 1 501	water [or shower].
P305 + P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, ij
	present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
2.3 Other ha	
	BT and vPvB assessment
PBT: Not ap	

*PBT:* Not applicable. · vPvB: Not applicable.

# 3 Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:
-------------------------

· Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	<i>Hydrocarbons, C9, aromatics</i>	10-25%
	(Con	td. on page 3



Version number 3

Revision: 15.05.2023

#### Trade name: SWIN UNIVERSAL EP HÄRTER

	(Cont	td. of page 2)
CAS: 157707-73-8 NLP: 500-382-3 Page mm : 01 2110072224 26 YYYY	C18-unsatd., branched and linear, tetraethylenepentamine and triethylenetetramine	
Reg.nr.: 01-2119972324-36-XXXX CAS: 71-36-3 EINECS: 200-751-6 Pag.nr.: 01-2110484630-38_XXXX	<ul> <li>♦ Eye Dam. 1, H318</li> <li>butan-1-ol</li> <li>♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox.</li> <li>4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336</li> </ul>	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	<i>n</i> -butyl acetate ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	2.5-10%
CAS: 90-72-2 EINECS: 202-013-9 Reg.nr.: 01-2119560597-27-XXXX	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1C, H314; Eye Dam. 1, H318;  Acute Tox. 4, H302; Skin Sens. 1B, H317	2.5-10%
CAS: 112-57-2 EINECS: 203-986-2 Reg.nr.: 01-2119972324-36-XXXX	3,6,9-triazaundecamethylenediamine ♦ Skin Corr. 1B, H314; ♦ Aquatic Chronic 2, H411; ↑ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	<i>≤</i> 2.5%
• Additional information: For the wo	ording of the listed hazard phrases refer to section 16.	<u> </u>

#### 4 First aid measures

• 4.1 Description of first aid measures

- · General information: Personal protection for the First Aider.
- After inhalation:
- Supply fresh air.
- Seek medical treatment in case of complaints.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- If skin irritation continues, consult a doctor.
- After eye contact:
- Rinse opened eye for several minutes under running water.

Seek medical treatment.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **5** Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- *Protective equipment:* Mouth respiratory protective device.

#### 6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

GB



Version number 3

Revision: 15.05.2023

#### Trade name: SWIN UNIVERSAL EP HÄRTER

Dispose contaminated material as waste according to section 13. • <b>6.4 Reference to other sections</b> See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.	(Contd. of page 3)

### 7 Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Restrict the quantity stored at the work place.

• Information about fire - and explosion protection: Fumes can combine with air to form an explosive mixture. Flammable gas-air mixtures may form in empty receptacles. Keep ignition sources away - Do not smoke. Use explosion-proof apparatus / fittings and spark-proof tools. Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• *Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor. Suitable material for receptacles and pipes: steel or stainless steel.* 

• Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

• 7.3 Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

#### 71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm Sk

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eves and skin.

• Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A2/P2

(Contd. on page 5)

GB



Version number 3

Revision: 15.05.2023

(Contd. of page 4)

Trade name: SWIN UNIVERSAL EP HÄRTER

#### • Protection of hands:

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material:  $\geq 0.4 \text{ mm}$ 

- · Penetration time of glove material
- *Value for the permeation: Level*  $\leq l$

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact => 480 minutes gloves made of the following materials are suitable: HPPE-laminatet film (Ansell Barrier®)
- Eye protection:



Tightly sealed goggles

#### · Body protection:

Protective clothing, anti-static (TYVEK® CLASSIC PLUS) Safety shoes/boots, antstatic

### 9 Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information

General Information	
· Appearance:	
Form:	Fluid
Colour:	Colourless
· Odour:	Aromatic
• Odour threshold:	Not determined.
· pH-value	Not applicable.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range.	: 116 °C
· Flash point:	23 - 60 °C
· Flammability (solid, gas):	Flammable.
• Auto-ignition temperature:	225 °C
• Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of explosive air, vapour mixtures are possible.
	(Contd. on page 6

(Contd. on page 6)

GB



Version number 3

Revision: 15.05.2023

Trade name: SWIN UNIVERSAL EP HÄRTER

	(Contd. of	page 5
· Explosion limits:		
Lower:	0.6 Vol %	
Upper:	10.8 Vol %	
· Vapour pressure at 20 °C:	6.7 hPa	
· Vapour pressure:		
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 °C:	11 s (DIN 53211/4)	
· 9.2 Other information	No further relevant information available.	

### **10 Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### 1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

- Primary irritant effect:
- Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Causes serious eye aamage.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction. • Additional toxicological information:
- Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- $\cdot$  Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure

(Contd. on page 7)

May cause damage to organs through prolonged or repeated exposure.

GB



Version number 3

Revision: 15.05.2023

Trade name: SWIN UNIVERSAL EP HÄRTER

• Aspiration hazard

May be fatal if swallowed and enters airways.

## **12 Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### **13 Disposal considerations**

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

- 15 01 00: packaging (including separately collected municipal packaging waste)
- 15 01 10\*: packaging containing residues of or contaminated by dangerous substances
- Recommendation: Disposal must be made according to official regulations.

1 / 7	· · ·	C	. •
14 Trans	nort in	tormai	101
I I I WINS		, <i>01 11 1</i> 11 1	1011

1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
PAINT RELATED MATERIAL
3 Flammable liquids.
3
III

(Contd. of page 6)



Version number 3

Revision: 15.05.2023

#### Trade name: SWIN UNIVERSAL EP HÄRTER

	(Contd. of p
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Segregation groups	(SGG18) Alkalis
Stowage Category	A
14.7 Transport in bulk according to Annex II o	f
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
4DR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(EQ)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

## **15 Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Information about limitation of use:
- Employment restrictions concerning pregnant and lactating women must be observed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

(Contd. on page 9)

GB



Version number 3

Revision: 15.05.2023

### Trade name: SWIN UNIVERSAL EP HÄRTER

(Contd. of	page 8)
H332 Harmful if inhaled.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H373 May cause damage to organs through prolonged or repeated exposure.	
H411 Toxic to aquatic life with long lasting effects.	
Department issuing SDS: -	
· Contact: -	
· Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concern	ing the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Lig. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Skin Corr. 1C: Skin corrosion/irritation – Category 1C	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1. Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
	GB