

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short
Revision date : 20.01.2023
Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SWIN 60-102-6
universal thinner short (12739)
N-BUTYL ACETATE ; CAS No. : 123-86-4 ; EC No. : 204-658-1 ; Index No. : 607-025-00-1 ; REACH No. : 01-2119485493-29

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Washing and cleaning products

1.3 Details of the supplier of the safety data sheet

Supplier

SWIN Lacksysteme
Inh. Ludwig Schöne e.K

Street : Boschweg 5

Postal code/City : 48351 Everswinkel

Telephone : +49(0)2582/67613

Telefax : +49(0)258267677

Information contact : info@swinsysteme.de

1.4 Emergency telephone number

Poison Information Center Göttingen (GIZ-Nord) Phone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.
STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Exclamation mark (GHS07)

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P312 Call a POISON CENTER/doctor if you feel unwell.
P370+P378 In case of fire: Use foam to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short
Revision date : 20.01.2023
Version (Revision) : 3.1.0 (3.0.0)
Print date : 04.04.2023

P501 Dispose of contents/container to disposal.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : N-BUTYL ACETATE

Index No. : 607-025-00-1

EC No. : 204-658-1

REACH No. : 01-2119485493-29

CAS No. : 123-86-4

Purity : 100 % [mass]

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove affected person from the danger area and lay down. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

Following inhalation

Inhalation of vapours or spray/mists

Consult a doctor immediately in the case of inhaling spray mist and show him packing or label. Provide fresh air.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness Headache Nausea Impairment of vision Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short

Revision date : 20.01.2023

Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Pyrolysis products, toxic Carbon monoxide Carbon dioxide (CO₂)

5.3 Advice for firefighters

Do not inhale explosion and combustion gases.
Special protective equipment for firefighters
Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

For non-emergency personnel

Use personal protection equipment. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

For emergency responders

Use appropriate respiratory protection. Remove persons to safety. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Clear contaminated areas thoroughly.

6.4 Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment (refer to section 8). Avoid: generation/formation of aerosols

It is recommended to design all work processes always so that the following is excluded: Inhalation Skin contact Eye contact

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists
Skin contact Eye contact Take precautionary measures against static discharges.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Usual measures for fire prevention. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of heat (e.g. hot surfaces), sparks

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short
Revision date : 20.01.2023
Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

and open flames. Provide earthing of containers, equipment, pumps and ventilation facilities. Use only antistatically equipped (spark-free) tools. Wear anti-static footwear and clothing. Take precautionary measures against static discharges.

Measures to prevent aerosol and dust generation

Vapours/aerosols must be exhausted directly at the point of origin. Use only in well-ventilated areas.

Environmental precautions

Shafts and sewers must be protected from entry of the product.

7.2 Conditions for safe storage, including any incompatibilities

Hints on joint storage

Storage class (TRGS 510) : 3

Further information on storage conditions

Keep container tightly closed. Keep/Store only in original container.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 (D)

Limit value : 62 ppm / 300 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 23.06.2022

Limit value type (country of origin) : STEL (EC)

Limit value : 150 ppm / 723 mg/m³

Version : 20.06.2019

Limit value type (country of origin) : STEL (EC)

Limit value : 150 ppm / 723 mg/m³

Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)

Limit value : 50 ppm / 241 mg/m³

Version : 20.06.2019

Limit value type (country of origin) : TWA (EC)

Limit value : 50 ppm / 241 mg/mg

Version : 20.06.2019

DNEL-/PNEC-values

DNEL/DMEL

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 600 mg/m³

Limit value type : DNEL worker (local)

Exposure route : Inhalation

Exposure frequency : Long-term

Limit value : 300 mg/m³

Limit value type : DNEL worker (systemic)

Exposure route : Inhalation

Exposure frequency : Short-term

Limit value : 600 mg/m³

Limit value type : DNEL worker (systemic)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short

Revision date : 20.01.2023

Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 300 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 11 mg/kg
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 11 mg/kg

PNEC

Limit value type : PNEC (Aquatic, freshwater)
Limit value : 0,18 mg/l
Limit value type : PNEC (Aquatic, marine water)
Limit value : 0,018 mg/l
Limit value type : PNEC (Sediment, freshwater)
Limit value : 0,981 mg/kg
Limit value type : PNEC (Soil)
Limit value : 0,0903 mg/kg
Limit value type : PNEC Soil, Marine water
Limit value : 0,0981 mg/kg
Limit value type : PNEC (Sewage treatment plant)
Limit value : 35,6 mg/l

8.2 Exposure controls



Personal protection equipment

Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable material : Butyl caoutchouc (butyl rubber)

Thickness of the glove material : 0.7 mm

Breakthrough time : 480 min

Recommended glove articles EN ISO 374

Remark : Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Overall

Suitable protective clothing : For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes). Chemical resistant safety shoes Only wear fitting, comfortable and clean protective clothing.

Required properties : antistatic. flame-resistant heat-resistant

Respiratory protection

Appropriate engineering controls

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection necessary at: exceeding exposure limit values aerosol or mist formation. spray application

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short
Revision date : 20.01.2023
Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter:
Filter type: A2P2

General information

Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid

Odour : characteristic

Appearance

Colour : colourless

Safety characteristics

| | | | | |
|--|--------------|--|------------------|-----------------------------|
| Melting point/freezing point : | | -78 | °C | |
| Initial boiling point and boiling range : | (1013 hPa) | 127 | °C | |
| Decomposition temperature : | | No data available | | |
| Flash point : | | 27 | °C | DIN 51755 part 1 |
| Auto-ignition temperature : | | 415 | °C | DIN 51794 |
| Lower explosion limit : | | 1,2 | Vol-% | |
| Upper explosion limit : | | 7,5 | Vol-% | |
| Lower explosion limit : | | 58 | g/m ³ | |
| Upper explosion limit : | | 360 | g/m ³ | |
| Vapour pressure : | (20 °C) | approx. | 12,5 | hPa |
| Density : | (20 °C) | approx. | 0,88 | g/cm ³ DIN 51757 |
| Relative density : | (20 °C) | No data available | | |
| Water solubility : | (20 °C) | | 5,3 | g/l |
| pH-value: | (20 °C) | | not applicable | |
| Partition coefficient n-octanol/water : | | | 2,3 | |
| Cinematic viscosity : | (40 °C) | No data available | | |
| Relative vapour density : | (20 °C) | No data available | | |
| Vapourisation rate : | | No data available | | |
| Maximum VOC content (EC) : | | 100 | Weight-% | 1999/13/EC |
| VOC-value : | | 881 | g/l | 2004/42/EC |
| Flammable solids : | | Not fulfilling criteria for hazard class "Flammable Solids". | | |
| Flammable gases : | | Not applicable. | | |
| Oxidising liquids : | | GHS/CLP criteria are not met. | | |
| Explosive properties : | | GHS/CLP criteria are not met. | | |

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

Information is given in subsection 10.3.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

In use, may form flammable/explosive vapour-air mixture.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short

Revision date : 20.01.2023

Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Exothermic reaction with:
Acid , Oxidising agent, strong.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Acute oral toxicity

| | |
|------------------|---|
| Parameter : | LD50 |
| Exposure route : | Oral |
| Species : | Rat |
| Effective dose : | 10760 mg/kg |
| Method : | OECD 423 |
| Parameter : | LD50 |
| Exposure route : | Oral |
| Species : | Rabbit |
| Effective dose : | 7,4 g/kg |
| Parameter : | LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4) |
| Exposure route : | Oral |
| Species : | Rat |
| Effective dose : | 10760 mg/kg |
| Method : | OECD 423 |
| Parameter : | LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4) |
| Exposure route : | Oral |
| Species : | Rabbit |
| Effective dose : | 7,4 g/kg |

Acute dermal toxicity

| | |
|------------------|---|
| Parameter : | LD50 |
| Exposure route : | Dermal |
| Species : | Rabbit |
| Effective dose : | > 14112 mg/kg |
| Method : | OECD 402 |
| Parameter : | LD50 (N-BUTYL ACETATE ; CAS No. : 123-86-4) |
| Exposure route : | Dermal |
| Species : | Rabbit |
| Effective dose : | > 14112 mg/kg |
| Method : | OECD 402 |

Acute inhalation toxicity

| | |
|------------------|---|
| Parameter : | LC50 |
| Exposure route : | Inhalation (dust/mist) |
| Species : | Rat |
| Effective dose : | 23,4 mg/l |
| Exposure time : | 4 h |
| Method : | OECD 403 |
| Parameter : | LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4) |
| Exposure route : | Inhalation (dust/mist) |
| Species : | Rat |
| Effective dose : | 23,4 mg/l |

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short
Revision date : 20.01.2023
Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

Exposure time : 4 h
Method : OECD 403

Corrosive/irritant effect on skin/eyes

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Based on available data, the classification criteria are not met.

Acute (short-term) fish toxicity

Parameter : LC50
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 18 mg/l
Exposure time : 96 h
Method : OECD 203
Parameter : LC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 18 mg/l
Exposure time : 96 h
Method : OECD 203

Acute (short-term) toxicity to crustacea

Parameter : EC50
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 44 mg/l
Exposure time : 48 h
Method : OECD 202
Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 44 mg/l
Exposure time : 48 h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short

Revision date : 20.01.2023

Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

Method : OECD 202

Chronic (long-term) toxicity to aquatic invertebrate

Parameter : NOEC

Species : Daphnia magna (Big water flea)

Evaluation parameter : Chronic (long-term) daphnia toxicity

Effective dose : 23 mg/l

Exposure time : 21 D

Method : OECD 211

Parameter : EL10

Species : Daphnia magna (Big water flea)

Evaluation parameter : Chronic (long-term) daphnia toxicity

Effective dose : 34,2 mg/l

Exposure time : 21 D

Method : OECD 211

Parameter : NOEC (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Daphnia magna (Big water flea)

Evaluation parameter : Chronic (long-term) daphnia toxicity

Effective dose : 23 mg/l

Exposure time : 21 D

Method : OECD 211

Parameter : EL10 (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Daphnia magna (Big water flea)

Evaluation parameter : Chronic (long-term) daphnia toxicity

Effective dose : 34,2 mg/l

Exposure time : 21 D

Method : OECD 211

Acute (short-term) toxicity to algae and cyanobacteria

Parameter : EC50

Species : Selenastrum capricornutum

Evaluation parameter : Acute (short-term) algae toxicity

Effective dose : 397 mg/l

Exposure time : 72 h

Method : OECD 201

Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Selenastrum capricornutum

Evaluation parameter : Acute (short-term) algae toxicity

Effective dose : 397 mg/l

Exposure time : 72 h

Method : OECD 201

Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter : NOEC

Species : Selenastrum capricornutum

Evaluation parameter : Chronic (long-term) algae toxicity

Effective dose : 196 mg/l

Method : OECD 201

Parameter : NOEC (N-BUTYL ACETATE ; CAS No. : 123-86-4)

Species : Selenastrum capricornutum

Evaluation parameter : Chronic (long-term) algae toxicity

Effective dose : 196 mg/l

Method : OECD 201

Toxicity to other aquatic plants/organisms

Parameter : EC50

Species : Tetrahymena pyriformis

Evaluation parameter : Acute (short-term) toxicity

Effective dose : 356 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short
Revision date : 20.01.2023
Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

Exposure time : 40 h
Parameter : EC50 (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Species : Tetrahymena pyriformis
Evaluation parameter : Acute (short-term) toxicity
Effective dose : 356 mg/l
Exposure time : 40 h

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 83 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301D

Parameter : BOD (% of ThOD)
Inoculum : Degree of elimination
Evaluation parameter : Aerobic
Degradation rate : 80 %
Test duration : 5 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301D

Parameter : Biodegradation (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Inoculum : Biodegradation
Evaluation parameter : Aerobic
Degradation rate : 83 %
Test duration : 28 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301D

Parameter : BOD (% of ThOD) (N-BUTYL ACETATE ; CAS No. : 123-86-4)
Inoculum : Degree of elimination
Evaluation parameter : Aerobic
Degradation rate : 80 %
Test duration : 5 D
Evaluation : Readily biodegradable (according to OECD criteria).
Method : OECD 301D

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short
Revision date : 20.01.2023
Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

SECTION 14: Transport information

14.1 UN number or ID number

UN 1123

14.2 UN proper shipping name

Land transport (ADR/RID)

BUTYL ACETATES

Sea transport (IMDG)

BUTYL ACETATES

Air transport (ICAO-TI / IATA-DGR)

BUTYL ACETATES

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special Provisions : LQ 5 I · E 1
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-D
Special Provisions : LQ 5 I · E 1
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special Provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No

Sea transport (IMDG) : No

Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 40

Other regulations (EU)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short

Revision date : 20.01.2023

Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

Restrictions of use in accordance with regulation (EC) 2019/1148 on the marketing and use of explosives precursors

None

Labelling for contents according to regulation (EC) No. 648/2004

None

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

No allocation to the classes I, II and III.

Water hazard class

Classification according to AwSV - Class : 1 (Slightly hazardous to water)

15.2 Chemical Safety Assessment

For this substance / mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
AGW = Occupational Exposure Limits
ATE = Acute Toxicity Estimates
AwSV = Ordinance on facilities for the handling of substances hazardous to water
DMEL = Derived Minimal Effect Levels
DNEL = Derived No Effect Level
ECx = effective concentration
H (8.1) = skin resorptive / risk of skin absorption
IATA = International Air Transport Association
ICAO = International Civil Aviation Organization
IMDG = International Maritime Code for Dangerous Goods
LCx/LDx/LLx = Lethal Concentration/Dose/Loading for x % of a population of test organisms
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEC/NOAEL = No Observed Adverse Effect Concentration/Level
NOEC/NOEL = No Observed Effect Concentration/Level
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, bioaccumulative and toxic
PNEC = Predicted No Effect Concentration
RID = Règlement concernant le transport international ferroviaire des marchandises dangereuses
RCP = reciprocal calculation procedure
S(a/h/ah) (8.1) = risk of sensitisation (of the respiratory tract/of the skin/of the respiratory tract and the skin)
SVHC = Substances of Very high Concern
STEL = Short-Time-Exposure Limit
TRGS = Technical rules for hazardous substances
TWA = Time Weighted Average
VOC = volatile organic compounds
vPvB = very persistent and very bioaccumulative
VwVwS = Administrative regulation of substances hazardous to water
WGK = water hazard class acc. ordinance on facilities for handling substances that are hazardous to water (AwSV)
Y (8.1) = No risk of fetal damage will have to be feared, if the occupational exposure limit values (AGW) and the biological limit values (BGW) are observed.
Z (8.1) = The risk of fetal damage must be feared, even if the occupational exposure limit values (AGW) and the biological limit values (BGW) are observed.

16.3 Key literature references and sources for data

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : SWIN 60-102-6
universal thinner short

Revision date : 20.01.2023

Print date : 04.04.2023

Version (Revision) : 3.1.0 (3.0.0)

None

16.4 Relevant H- and EUH-phrases (Number and full text)

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

16.5 Training advice

None

16.6 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
