

Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

1 Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier CODE 1000

· Trade name: SWIN MISCHLACK

· Article number: SW-XXXX-*

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- Environmental release category ERC8c Widespread use leading to inclusion into/onto article (indoor)
- · Application of the substance / the mixture Coating material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SWIN Lacksysteme

Boschweg 5

D-48351 Everswinkel

info@swinsysteme.de

- Further information obtainable from: +49 2582-67613 / +49 2582-67677
- · 1.4 Emergency telephone number:

Giftinformationszentrum Göttingen (GIZ-Nord) Phone: +49 (0)551-19240

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

n-butvl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)



Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

Trade name: SWIN MISCHLACK

(Contd. of page 1) P240 Ground and bond container and receiving equipment. P241 Use explosion-proof [electrical/ventilating/lighting] equipment. P243 Take action to prevent static discharges. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards -
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene ♠ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47-XXXX	2-butoxyethyl acetate	≤2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · General information: Personal protection for the First Aider.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB



Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

Trade name: SWIN MISCHLACK

(Contd. of page 2)

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Restrict the quantity stored at the work place.

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

Keep ignition sources away - Do not smoke.

Use explosion-proof apparatus / fittings and spark-proof tools.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Suitable material for receptacles and pipes: steel or stainless steel.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)



Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

Trade name: SWIN MISCHLACK

(Contd. of page 3)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

 $Do \ not \ inhale \ gases \ / \ fumes \ / \ aerosols.$

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P2

· Protection of hands:

Only use chemical-protective gloves with CE-labelling of category III.



Protective gloves

Preventive skin protection by use of skin-protecting agents is recommended.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be exactly calculated in advance and has therefore to be checked prior to the application.

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber (Ansell Sol-Vex®)

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

Value for the permeation: Level ≤ 1

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact => 480 minutes gloves made of the following materials are suitable:

HPPE-laminatet film (Ansell Barrier®)

· Eye protection:



Tightly sealed goggles

· Body protection:

Protective clothing, anti-static (TYVEK® CLASSIC PLUS) Safety shoes/boots, antstatic

- G



Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

Trade name: SWIN MISCHLACK

(Contd. of page 4)

9.1 Information on basic physical and	chemical properties
General Information	F. of const
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Aromatic
Odour threshold:	Not determined.
pH-value	Not applicable.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling rang	re: 124 °C
Flash point:	23 - 60 °C
Flammability (solid, gas):	Flammable.
Auto-ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Vapour pressure:	
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	DIN 53211 (6 mm) - 38 sec
Dynamic:	Not determined.
Kinematic at 20 °C:	100 s (ISO 6 mm)

10 Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.



Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

Trade name: SWIN MISCHLACK

(Contd. of page 5)

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal		>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

15 00 00: WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00: packaging (including separately collected municipal packaging waste)

15 01 10*: packaging containing residues of or contaminated by dangerous substances

· Recommendation: Disposal must be made according to official regulations.

GB



Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

Trade name: SWIN MISCHLACK

(Contd. of page 6)

Transport information	
· 14.1 UN-Number · ADR, ADN, IMDG · IATA	not regulated UN1263
· 14.2 UN proper shipping name · ADR, ADN, IMDG · IATA	not regulated PAINT
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG · Class	not regulated
· IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG · IATA	not regulated III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.
· Transport/Additional information:	
· ADR · Remarks:	No dangerous goods in containers of 450 litres max capacity acc. to ADR 2.2.3.1.5.1
· IMDG · Remarks:	No dangerous goods in containers of 30 litres ma: capacitiy acc. to IMDG 2.2.3.1.5
· UN "Model Regulation":	not regulated

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:
- · Information about limitation of use:

 $\label{lem:employment} \textit{Employment restrictions concerning pregnant and lactating women must be observed.}$

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 17.05.2023 Version number 3 Revision: 17.05.2023

Trade name: SWIN MISCHLACK

(Contd. of page 7)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Department issuing SDS: -

· Contact: -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1